

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Reference number: ALC-117 Issue date: 11/23/2020 Version: 1.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form : Mixture

Product name : ALCON AL-680 RED PENETRANT SPRAY

Product code : M-7726
Vaporizer : Aerosol
Product group : Trade product

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

### 1.2.1. Relevant identified uses

Main use category : Industrial use, Consumer use

Industrial/Professional use spec : Industrial

Use of the substance/mixture : With its special formulation, AL-680 Red Penetrant Spray serves to inspect the pores and

cracks that occur before or during welding. It penetrates even into the most difficult parts

and brings the cracks to daylight.

#### 1.2.2. Uses advised against

No additional information available

### 1.3. Details of the supplier of the safety data sheet

ALCON ENDÜSTRİYEL ÜRÜNLER SANAYİ VE TİCARET LİMİTED ŞİRKETİ SOĞANLIK YENİ MAH, ALİAĞA SOK. NO:8 KAT:9 DAİRE:37 Bumerang Kartal Rezidans 34880 KARTAL / İSTANBUL - TÜRKİYE T +90 216 661 00 90 - F +90 216 661 01 57

T +90 216 661 00 90 - F +90 216 661 01 57 alcon@alcon.com.tr - www.alcon.com.tr

### 1.4. Emergency telephone number

Emergency number : +90 216 661 00 90

Country	Organisation/Company	Address	Emergency number	Comment
Turkey	Ulusal Zehir Merkezi (UZEM) Refik Saydam Hıfzıssıhha Merkezi Başkanlığı	Cemal Gürsel Cd. No: 18 Sıhhiye Çankaya 06590 Ankara	114	Information is provided to public and medical personnel on poisoning incidents via 114.

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229
Serious eye damage/eye irritation, Category 2 H319
Skin sensitisation, Category 1 H317
Hazardous to the aquatic environment — Chronic Hazard, Category 3 H412

Full text of H statements : see section 16

### Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause an allergic skin reaction. Causes serious eye irritation. Harmful to aquatic life with long lasting effects.

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 2.2. Label elements

### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)





GHS02

S02 GHS07

Signal word (CLP) : Danger

Contains : N-(2-ethylhexyl)-1-[[3-methyl-4-[(3-methylphenyl)azo]phenyl]azo]naphthalen-2-amine

Hazard statements (CLP) : H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated. H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation. H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

### 2.3. Other hazards

No additional information available

### **SECTION 3: Composition/information on ingredients**

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
butane (Note C)(Note U)	(CAS-No.) 106-97-8 (EC-No.) 203-448-7 (EC Index-No.) 601-004-00-0	25 – 50	Flam. Gas 1, H220 Press. Gas
2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether	(CAS-No.) 112-34-5 (EC-No.) 203-961-6 (EC Index-No.) 603-096-00-8	10 – 25	Eye Irrit. 2, H319
propane (Note U)	(CAS-No.) 74-98-6 (EC-No.) 200-827-9 (EC Index-No.) 601-003-00-5	2.5 – 10	Flam. Gas 1, H220 Press. Gas
Distillates (petroleum), hydro- treated light; Kerosine—unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approxi mately 150 °C to 290 °C (302 °F to 554 °F).]	(CAS-No.) 64742-47-8 (EC-No.) 265-149-8 (EC Index-No.) 649-422-00-2	2.5 – 10	Asp. Tox. 1, H304

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hydrocarbons, C10, aromatics, <1% naphthalene	(EC-No.) 918-811-1	2.5 – 10	Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 2, H411 (M=0)
isobutane (Note C)(Note U)	(CAS-No.) 75-28-5 (EC-No.) 200-857-2 (EC Index-No.) 601-004-00-0	0.1 – 2.5	Flam. Gas 1, H220 Press. Gas
N-(2-ethylhexyl)-1-[[3-methyl-4-[(3-methylphenyl)azo]phenyl]azo]naphthalen-2-amine	(CAS-No.) 56358-10-2 (EC-No.) 260-125-3	1 – 2.5	Skin Irrit. 2, H315 Skin Sens. 1, H317

Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note U (Table 3): When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H-statements: see section 16

### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash

occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact : May cause an allergic skin reaction.

Symptoms/effects after eye contact : Eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide. Unsuitable extinguishing media : Do not use a water jet as it may cause spread.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Pressurised container: May burst if heated.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

11/23/2020 (Version: 1.0) EN (English) 3/12

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin

and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Mechanically recover the product.

Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear personal protective

equipment.

Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash

contaminated clothing before reuse. Do not eat, drink or smoke when using this product.

Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place. Keep cool.

### 7.3. Specific end use(s)

No additional information available

### **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether (112-34-5)	
EU - Occupational Exposure Limits	
Local name	2-(2-Butoxyethoxy)ethanol
IOELV TWA (mg/m³)	67.5 mg/m³
IOELV TWA (ppm)	10 ppm
IOELV STEL (mg/m³)	101.2 mg/m³
IOELV STEL (ppm)	15 ppm
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether (112-34-5)	
Turkey - Occupational Exposure Limits	
Local name 2-(2-Bütoksietoksi)etanol	
OEL TWA (mg/m³)	67.5 mg/m³
OEL TWA (ppm)	10 ppm
OEL STEL (mg/m³)	101.2 mg/m³
OEL STEL (ppm) 15 ppm	
Regulatory reference	12 Ağustos 2013 Tarihli ve 28733 Sayılı Resmî Gazete

### 8.2. Exposure controls

### Appropriate engineering controls:

Ensure good ventilation of the work station.

Hand protection:	
Protective gloves	

Eye protection:	
Safety glasses	

### Skin and body protection:

Wear suitable protective clothing

### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

### Personal protective equipment symbol(s):



### Environmental exposure controls:

Avoid release to the environment.

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid Appearance : Aerosol liquid. Colour : Red. Odour : Characteristic. Odour threshold : No data available : No data available рΗ Relative evaporation rate (butylacetate=1) : No data available Melting point : Not applicable Freezing point : No data available Boiling point : No data available Flash point : No data available

Auto-ignition temperature : No data available Decomposition temperature : No data available

Flammability (solid, gas) : Extremely flammable aerosol.

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Vapour pressure : 2.5 - 5 bar (At 20 ° C) Relative vapour density at 20 °C : No data available Relative density : No data available

Density :  $0.7 - 0.8 \text{ g/cm}^3 \text{ (At } 20 \degree \text{ C)}$ 

Solubility : No data available
Partition coefficient n-octanol/water (Log Pow) : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available

Explosive properties : Pressurised container: May burst if heated.

Oxidising properties : No data available Explosive limits : No data available

### 9.2. Other information

No additional information available

### **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

### 2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether (112-34-5)

LD50 dermal rabbit 2764 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), 95% CL: 2090 - 3645

Distillates (petroleum), hydro- treated light; Kerosine— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approxi mately 150 °C to 290 °C (302 °F to 554 °F).] (64742-47-8)

LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.1175 (Acute Oral Toxicity), Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: EPA OTS 798.1100 (Acute Dermal Toxicity), Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

### Safety Data Sheet

Reproductive toxicity

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

LC50 Inhalation - Rat	> 5.28 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity),
	95% CL: 0,42 -

Hydrocarbons, C10, aromatics, <1% naphthalene	
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified Carcinogenicity : Not classified

Distillates (petroleum), hydro- treated light; Kerosine— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approxi mately 150 °C to 290 °C (302 °F to 554 °F).] (64742-47-8)

: Not classified

NOAEL (animal/male, F0/P) ≥ 3000 mg/kg bodyweight Animal: rat, Animal sex: male

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

### 2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether (112-34-5)

NOAEL (oral, rat, 90 days)
250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity

Day Oral Toxicity in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPPTS

870.3100 (90-Day Oral Toxicity in Rodents)

Distillates (petroleum), hydro- treated light; Kerosine— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approxi mately 150 °C to 290 °C (302 °F to 554 °F).] (64742-47-8)

NOAEL (oral, rat, 90 days)	750 mg/kg bodyweight Animal: rat, Animal sex: female
NOAEC (inhalation, rat, vapour, 90 days)	≥ 0.024 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

Hydrocarbons, C10, aromatics, <1% naphthalene	
` ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' '	300 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90- Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)

Aspiration hazard : Not classified

### **ALCON AL-680 RED PENETRANT SPRAY**

Vaporizer Aerosol

### **SECTION 12: Ecological information**

### 12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term : Not classified

(acute)

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hazardous to the aquatic environment, long-term :

: Harmful to aquatic life with long lasting effects.

(chronic)

Not rapidly degradable

2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether (112-34-5)	
LC50 fish 1	1300 mg/l Test organisms (species): Lepomis macrochirus
EC50 Daphnia 1	> 100 mg/l Test organisms (species): Daphnia magna
EC50 96h algae (1)	> 100 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

No additional information available

### **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

Waste treatment methods

: Dispose of contents/container in accordance with licensed collector's sorting instructions.

### **SECTION 14: Transport information**

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number	I4.1. UN number			
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shippin	g name			
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document descr	iption			
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1
14.3. Transport hazard o	14.3. Transport hazard class(es)			
2.1	2.1	2.1	2.1	2.1
2	2	2	2	2
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

14.5. Environmental hazards				
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR) : 5F

Special provisions (ADR) : 190, 327, 344, 625

Limited quantities (ADR) : 1I Excepted quantities (ADR) : E0

Packing instructions (ADR) : P207, LP200 Special packing provisions (ADR) : PP87, RR6, L2

Mixed packing provisions (ADR) : MP9
Transport category (ADR) : 2
Special provisions for carriage - Packages (ADR) : V14
Special provisions for carriage - Loading, unloading : CV9, CV12

and handling (ADR)

Special provisions for carriage - Operation (ADR) : S2
Tunnel restriction code (ADR) : D

Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959

Packing instructions (IMDG) : P207, LP200
Special packing provisions (IMDG) : PP87, L2
EmS-No. (Fire) : F-D
EmS-No. (Spillage) : S-U
Stowage category (IMDG) : None
Stowage and handling (IMDG) : SW1, SW22
Segregation (IMDG) : SG69

Air transport

PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg

Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

Inland waterway transport

Classification code (ADN) : 5F

Special provisions (ADN) : 190, 327, 344, 625

Limited quantities (ADN) : 1 L

Excepted quantities (ADN) : E0

Equipment required (ADN) : PP, EX, A

Ventilation (ADN) : VE01, VE04

Number of blue cones/lights (ADN) : 1

Rail transport

Classification code (RID) : 5F

Special provisions (RID) : 190, 327, 344, 625

Limited quantities (RID) : 1L Excepted quantities (RID) : E0

Packing instructions (RID) : P207, LP200 Special packing provisions (RID) : PP87, RR6, L2

Mixed packing provisions (RID) : MP9
Transport category (RID) : 2
Special provisions for carriage – Packages (RID) : W14
Special provisions for carriage - Loading, unloading : CW9, CW12

and handling (RID)

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Colis express (express parcels) (RID) : CE2 Hazard identification number (RID) : 23

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

### **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:		
Reference code	Applicable on Entry title or description	
55.	2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether	2-(2-butoxyethoxy)ethanol (DEGBE)

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

### 15.1.2. National regulations

#### Germany

Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG)

Observe restrictions according Act on the Protection of Young People in Employment

(JArbSchG)

Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1)
Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

SZW-lijst van kankerverwekkende stoffen : Dis

: Distillates (petroleum), hydro- treated light; Kerosine— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approxi mately 150 °C to 290 °C (302 °F to 554).

°F).] is listed

SZW-lijst van mutagene stoffen : Distil

: Distillates (petroleum), hydro- treated light; Kerosine— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approxi mately 150 °C to 290 °C (302 °F to 554).

°F).] is listed

NIET-limitatieve lijst van voor de voortplanting

giftige stoffen - Borstvoeding

NIET-limitatieve lijst van voor de voortplanting

giftige stoffen - Vruchtbaarheid

NIET-limitatieve lijst van voor de voortplanting

giftige stoffen - Ontwikkeling

: None of the components are listed

: None of the components are listed

: None of the components are listed

Denmark

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

### **SECTION 16: Other information**

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ATE	Acute Toxicity Estimate
BLV	Biological limit value
CAS-No.	Chemical Abstract Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
EC-No.	European Community number
EN	European Standard
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative
WGK	Water Hazard Class

Data sources

: REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Full text of H- and EUH-statements:		
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2	
Asp. Tox. 1	Aspiration hazard, Category 1	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
Flam. Gas 1	Flammable gases, Category 1	
Press. Gas	Gases under pressure	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
Skin Sens. 1	Skin sensitisation, Category 1	
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis	
H220	Extremely flammable gas.	
H222	Extremely flammable aerosol.	
H229	Pressurised container: May burst if heated.	

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

H304	May be fatal if swallowed and enters airways.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H336	May cause drowsiness or dizziness.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	

SDS EU (REACH Annex II)

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable