

ALCON ANAEROBIC HIGH STRENGTH THREADLOCKER 72.710 (Y.K.S) STEEL LOCK

Creation date	02nd March 2020	Version	3.0
Revision date	24th November 2025		

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier**
ALCON ANAEROBIC HIGH STRENGTH THREADLOCKER 72.710 (Y.K.S) STEEL LOCK
Substance / mixture mixture
Number M-5271 / M-7271 / M-8271
- 1.2. Relevant identified uses of the substance or mixture and uses advised against**
Mixture's intended use
It is used where studs and nuts are not to be removed up to 1 "(25 mm). It is generally used in engine stubs, cylinder block anchors, water pump coupling connections and white goods industry.
Mixture uses advised against
The product should not be used in ways other than those referred in Section 1.
- 1.3. Details of the supplier of the safety data sheet**
Manufacturer
Name or trade name ALCON ENDÜSTRİYEL ÜRÜNLER SAN. VE TİC. LTD. ŞTİ.
Address SOĞANLIK YENİ MAH. ALİAĞA SOK. NO:8 DAİRE:37 Bumerang Kartal Rezidans Kartal, İstanbul, 34880
Turkey
Phone +90 216 661 00 90
Email alcon@alcon.com.tr
Web address www.alcon.com.tr
- 1.4. Emergency telephone number**
European emergency number: 112

SECTION 2: Hazards identification

- 2.1. Classification of the substance or mixture**
Classification of the mixture in accordance with Regulation (EC) No 1272/2008
The mixture is classified as dangerous.

Skin Sens. 1, H317
Eye Irrit. 2, H319
STOT SE 3, H335
Most serious adverse effects on human health and the environment
May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation.
- 2.2. Label elements**
Hazard pictogram

Signal word
Warning
Hazardous substances
Methacrylic acid, monoester with propane-1,2-diol
 α , α -dimethylbenzyl hydroperoxide
cumene
Hazard statements
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ALCON ANAEROBIC HIGH STRENGTH THREADLOCKER 72.710 (Y.K.S) STEEL LOCK

Creation date 02nd March 2020 Version 3.0
Revision date 24th November 2025

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear eye protection/protective gloves.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
P501 Dispose of contents/container to be handed over to the person authorized to dispose of waste or by returning to the supplier.

2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended. Does not contain any PMT or vPvM components.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
CAS: 27813-02-1 EC: 248-666-3	Methacrylic acid, monoester with propane-1,2-diol	70-<90	Skin Sens. 1, H317 Eye Irrit. 2, H319	
Index: 617-002-00-8 CAS: 80-15-9 EC: 201-254-7	α , α -dimethylbenzyl hydroperoxide	1-<2	Org. Perox. E, H242 Acute Tox. 4, H302+H312 Skin Corr. 1B, H314 Acute Tox. 3, H331 STOT RE 2 (**), H373 Aquatic Chronic 2, H411 Specific concentration limit: Skin Irrit. 2, H315: 3 % $\leq$ C < 10 % Eye Irrit. 2, H319: 1 % $\leq$ C < 3 % STOT SE 3, H335: C < 10 % Eye Dam. 1, H318: 3 % $\leq$ C < 10 % Skin Corr. 1B, H314: C $\geq$ 10 %	
Index: 601-024-00-X CAS: 98-82-8 EC: 202-704-5	cumene	<0.1	Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H335 Carc. 1B, H350 Aquatic Chronic 2, H411	1, 2, 3

Notes

- ** another exposure route cannot be ruled out
1 A substance for which exposure limits are set.
2 Substance for which biological limit values exist.
3 The use of the substance is restricted by Annex XVII of REACH Regulation

Full text of all classifications and hazard statements is given in the section 16.

ALCON ANAEROBIC HIGH STRENGTH THREADLOCKER 72.710 (Y.K.S) STEEL LOCK

Creation date	02nd March 2020	Version	3.0
Revision date	24th November 2025		

SECTION 4: First aid measures**4.1. Description of first aid measures**

Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet. If unconscious, put the person in the stabilized (recovery) position on his side with his head slightly bent backwards and make sure that airways are free; never induce vomiting. If the person vomits by himself, make sure that the vomit is not inhaled. In life threatening conditions first of all provide resuscitation of the affected person and ensure medical assistance. Respiratory arrest - provide artificial respiration immediately. Cardiac arrest - provide indirect cardiac massage immediately.

If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Protect the person against growing cold. Provide medical treatment if irritation, dyspnoea or other symptoms persist.

If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible. Soap, soap solution or shampoo should be used if there is no skin injury. Provide medical treatment if skin irritation persists.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Rinsing should continue at least for 10 minutes. Provide medical treatment, specialized if possible.

If swallowed

Rinse out the mouth with water and provide 0.2-0.5 L of water. Provide medical treatment if the person has any health problems.

4.2. Most important symptoms and effects, both acute and delayed**If inhaled**

May cause respiratory irritation.

If on skin

May cause an allergic skin reaction.

If in eyes

Causes serious eye irritation.

If swallowed

Irritation, nausea.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

Unsuitable extinguishing media

Water - full jet.

5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes.

6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

ALCON ANAEROBIC HIGH STRENGTH THREADLOCKER 72.710 (Y.K.S) STEEL LOCK

Creation date	02nd March 2020	Version	3.0
Revision date	24th November 2025		

6.3. Methods and material for containment and cleaning up

Contain the spill and cover it with a non-flammable absorbent material such as sand, soil, vermiculite, or seaweed sand, etc. Place it in a container and dispose of it in accordance with local regulations. The contaminated area must be cleaned immediately with a suitable decontaminant. A possible (flammable) decontaminant consists of, by volume: water (45 parts), ethanol or isopropyl alcohol (50 parts), and concentrated (density: 0.880) ammonia solution (5 parts). After using the appropriate decontaminant, place the material in a sealable, labeled container for proper disposal.

6.4. Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Prevent formation of gases and vapours in concentrations exceeding the occupational exposure limits. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes. Wash hands and exposed parts of the body thoroughly after handling. Use only outdoors or in a well-ventilated area. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection.

7.2. Conditions for safe storage, including any incompatibilities

Store in the original containers at 8-21°C (46.4-69.8°F). Do not return unused material to the container, as contamination of the product contents may shorten its shelf life.

Storage temperature min 8 °C, max 21 °C

7.3. Specific end use(s)

It is used to secure pins, bushings, and cylindrical metal parts to the bearing or shaft.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

The mixture contains substances for which occupational exposure limits are set.

European Union**Commission Directive (EU) 2019/1831**

Substance name (component)	Type	Value
cumene (CAS: 98-82-8)	OEL 8 hours	50 mg/m ³
	OEL 8 hours	10 ppm
	OEL 15 minutes	250 mg/m ³
	OEL 15 minutes	50 ppm

Notes

During exposure monitoring, account should be taken of relevant biological monitoring values as suggested by the Scientific Committee on Occupational Exposure Limits for Chemicals Agents (SCOEL).

Skin.

European Union**Commission Directive 2000/39/EC**

Substance name (component)	Type	Value
cumene (CAS: 98-82-8)	OEL 8 hours	100 mg/m ³
	OEL 8 hours	20 ppm
	OEL 15 minutes	250 mg/m ³
	OEL 15 minutes	50 ppm

Notes

Skin.

Turkey

Substance name (component)	Type	Value
cumene (CAS: 98-82-8)	TWA (8 hours)	100 mg/m ³
	TWA (8 hours)	20 ppm

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ALCON ANAEROBIC HIGH STRENGTH THREADLOCKER 72.710 (Y.K.S) STEEL LOCK

Creation date 02nd March 2020 Version 3.0
 Revision date 24th November 2025

Turkey

Substance name (component)	Type	Value
cumene (CAS: 98-82-8)	STEL (15 min.)	250 mg/m ³
	STEL (15 min.)	50 ppm

Notes

.

Biological limit values

European Union

SCOEL

Name	Parameter	Value	Tested material	Time of sampling
cumene (CAS: 98-82-8)	2-phenyl-2-propanol	7 mg/g of creatinine	Urine	Between 2 and 4 hours after the end of exposure

8.2. Exposure controls

Take off contaminated clothing and wash before reuse. Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. If exposure limits cannot be observed in this mode, suitable protection of airways must be used. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

Eye/face protection



Protective goggles.

Skin protection



Hand protection: Protective gloves resistant to the product. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Contaminated skin should be washed thoroughly.

Glove material	Thickness	Breakthrough time	Class
Neoprene (CR)	≥ 0.7 mm	>30 min	2

Respiratory protection



Halfmask with a filter against organic vapours in the poorly ventilated environment.

ALCON ANAEROBIC HIGH STRENGTH THREADLOCKER 72.710 (Y.K.S) STEEL LOCK

Creation date	02nd March 2020	Version	3.0
Revision date	24th November 2025		

Thermal hazard

Not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state	liquid
Colour	red
Odour	Acrylate, characteristic
Melting point/freezing point	data not available
Boiling point or initial boiling point and boiling range	>149 °C
Flammability	data not available
Lower and upper explosion limit	data not available
Flash point	>100 °C
Auto-ignition temperature	data not available
Decomposition temperature	data not available
pH	data not available
Kinematic viscosity	data not available
Viscosity	7000 cPs at 20 °C
Solubility in water	data not available
Partition coefficient n-octanol/water (log value)	data not available
Vapour pressure	<666.6 Pa at 26.5 °C
Density and/or relative density	
Density	1.03 g/cm ³ at 20 °C
Relative vapour density	1.035
Particle characteristics	data not available

9.2. Other information

not available

SECTION 10: Stability and reactivity**10.1. Reactivity**

Keep away from oxidizing agents and strong acidic or alkaline substances. This product may react rapidly with these substances and carbon dioxide may form. Carbon dioxide formation in closed containers can lead to excessive pressure and consequently the risk of explosion.

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Unknown.

10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost.

10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.



SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ALCON ANAEROBIC HIGH STRENGTH THREADLOCKER 72.710 (Y.K.S) STEEL LOCK

Creation date 02nd March 2020 Version 3.0
Revision date 24th November 2025

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Hazardous substances in concentrations exceeding exposure limits may cause acute inhalation poisoning, depending on the concentration and duration of exposure. No toxicological data is available for the mixture.

Acute toxicity

Based on the available data, the criteria for classification of the mixture are not met. Data for the components of the mixture are not available.

ALCON ANAEROBIC HIGH STRENGTH THREADLOCKER 72.710 (Y.K.S) STEEL LOCK						
Route of exposure	Parameter	Value	Exposure time	Species	Sex	Value determination
Oral	ATE	25000 mg/kg				Calculation of value
Dermal	ATE	55000 mg/kg				Calculation of value
Inhalation (vapor)	ATE	150 mg/l				Calculation of value

Skin corrosion/irritation

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Serious eye damage/irritation

Causes serious eye irritation. Data for the components of the mixture are not available.

Respiratory or skin sensitisation

May cause an allergic skin reaction. Data for the components of the mixture are not available.

Germ cell mutagenicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Carcinogenicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Reproductive toxicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Toxicity for specific target organ - single exposure

May cause respiratory irritation. Data for the components of the mixture are not available.

Toxicity for specific target organ - repeated exposure

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Aspiration hazard

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

ALCON ANAEROBIC HIGH STRENGTH THREADLOCKER 72.710 (Y.K.S) STEEL LOCK

Creation date	02nd March 2020	Version	3.0
Revision date	24th November 2025		

11.2. Information on other hazards**Endocrine disrupting properties**

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any components that may cause endocrine disruption for humans.

Other information

not available

SECTION 12: Ecological information**12.1. Toxicity**

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

12.2. Persistence and degradability

No data are available for either the mixture or the components.

12.3. Bioaccumulative potential

No data are available for either the mixture or the components.

12.4. Mobility in soil

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any PMT or vPvM components.

12.5. Results of PBT and vPvB assessment

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any PBT or vPvB components.

12.6. Endocrine disrupting properties

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any components that may cause endocrine disruption in the environment.

12.7. Other adverse effects

Not available.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

Waste type code

08 04 09* waste adhesives and sealants containing organic solvents or other hazardous substances

15 01 10* packaging containing residues of or contaminated by hazardous substances

(*) - Hazardous waste according to Directive 2008/98/EC on hazardous waste

SECTION 14: Transport information**14.1. UN number or ID number**

not subject to transport regulations

14.2. UN proper shipping name

not relevant

14.3. Transport hazard class(es)

not relevant

14.4. Packing group

not relevant

ALCON ANAEROBIC HIGH STRENGTH THREADLOCKER 72.710 (Y.K.S) STEEL LOCK

Creation date	02nd March 2020	Version	3.0
Revision date	24th November 2025		

14.5. Environmental hazards

not relevant

14.6. Special precautions for user

Reference in the Sections 4 to 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

Restrictions pursuant to Annex XVII of Regulation (EC) No. 1907/2006 (REACH), as amended

cumene

Restriction	Conditions of restriction
28	1. Shall not be placed on the market, or used, — as substances, — as constituents of other substances, or, — in mixtures, for supply to the general public when the individual concentration in the substance or mixture is equal to or greater than: — either the relevant specific concentration limit specified in Part 3 of Annex VI to Regulation (EC) No 1272/2008, or, — the relevant generic concentration limit specified in Part 3 of Annex I of Regulation (EC) No 1272/2008. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that the packaging of such substances and mixtures is marked visibly, legibly and indelibly as follows: “Restricted to professional users”. 2. By way of derogation, paragraph 1 shall not apply to: (a) medicinal or veterinary products as defined by Directive 2001/82/EC and Directive 2001/83/EC; (b) cosmetic products as defined by Directive 76/768/EEC; (c) the following fuels and oil products: — motor fuels which are covered by Directive 98/70/EC, — mineral oil products intended for use as fuel in mobile or fixed combustion plants, — fuels sold in closed systems (e.g. liquid gas bottles); (d) artists' paints covered by Regulation (EC) No 1272/2008; (e) the substances listed in Appendix 11, column 1, for the applications or uses listed in Appendix 11, column 2. Where a date is specified in column 2 of Appendix 11, the derogation shall apply until the said date. (f) devices covered by Regulation (EU) 2017/745.

15.2. Chemical safety assessment

not available

SECTION 16: Other information**A list of standard risk phrases used in the safety data sheet**

H226

Flammable liquid and vapour.



SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ALCON ANAEROBIC HIGH STRENGTH THREADLOCKER 72.710 (Y.K.S) STEEL LOCK

Creation date	02nd March 2020	Version	3.0
Revision date	24th November 2025		

H242	Heating may cause a fire.
H302+H312	Harmful if swallowed or in contact with skin.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H350	May cause cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Guidelines for safe handling used in the safety data sheet

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear eye protection/protective gloves.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/container to by handing over to the person authorized to dispose of waste or by returning to the supplier.

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

Acute Tox.	Acute toxicity
ADR	Agreement concerning the international carriage of dangerous goods by road
Aquatic Chronic	Hazardous to the aquatic environment (chronic)
Asp. Tox.	Aspiration hazard
ATE	Acute toxicity estimate
BCF	Bioconcentration Factor
Carc.	Carcinogenicity
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
EC	Identification code for each substance listed in EINECS
EINECS	European Inventory of Existing Commercial Chemical Substances
EmS	Emergency Response Procedures for Ships Carrying Dangerous Goods
EU	European Union
EuPCS	European Product Categorisation System
Eye Dam.	Serious eye damage
Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquid
IATA	International Air Transport Association
IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
ICAO	International Civil Aviation Organization

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ALCON ANAEROBIC HIGH STRENGTH THREADLOCKER 72.710 (Y.K.S) STEEL LOCK

Creation date	02nd March 2020	Version	3.0
Revision date	24th November 2025		

IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization
IUPAC	International Union of Pure and Applied Chemistry
log Kow	Octanol-water partition coefficient
OEL	Occupational Exposure Limits
Org. Perox.	Organic peroxide
PBT	Persistent, bioaccumulative and toxic
PMT	Persistent, mobile and toxic
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulation concerning the International Carriage of Dangerous Goods by Rail
Skin Corr.	Skin corrosion
Skin Irrit.	Skin irritation
Skin Sens.	Skin sensitization
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure
UN number	Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB	Substances of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very persistent and very bioaccumulative
vPvM	Very persistent and very mobile

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended.
REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

More information

Classification procedure - calculation method.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.