

ALCON COPPER SUPER LEAK COOLING SYSTEM

Creation date	24th November 2020	Version	3.0
Revision date	21st November 2025		

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier** ALCON COPPER SUPER LEAK COOLING SYSTEM
Substance / mixture mixture
Number M-9905
- 1.2. Relevant identified uses of the substance or mixture and uses advised against**
Mixture's intended use
It is used to cover small holes and cracks in vehicle radiators.
Mixture uses advised against
The product should not be used in ways other than those referred in Section 1.
- 1.3. Details of the supplier of the safety data sheet**
Manufacturer
Name or trade name ALCON ENDÜSTRİYEL ÜRÜNLER SAN. VE TİC. LTD. ŞTİ.
Address SOĞANLIK YENİ MAH. ALİAĞA SOK. NO:8 DAİRE:37 Bumerang
Kartal Rezidans Kartal, İstanbul, 34880
Turkey
Phone +90 216 661 00 90
Email alcon@alcon.com.tr
Web address www.alcon.com.tr
- 1.4. Emergency telephone number**
European emergency number: 112

SECTION 2: Hazards identification

- 2.1. Classification of the substance or mixture**
Classification of the mixture in accordance with Regulation (EC) No 1272/2008
The mixture is classified as dangerous.
- Skin Corr. 1, H314
Skin Sens. 1A, H317
Eye Dam. 1, H318
STOT SE 3, H335
Aquatic Chronic 3, H412
- Most serious adverse effects on human health and the environment**
Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation. Harmful to aquatic life with long lasting effects.
- 2.2. Label elements**
Hazard pictogram
- 
- Signal word**
Danger
- Hazardous substances**
SODIUM SILICATE SOLUTION EXTRA PURE
Sodium dodecyl sulphate
copper
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
- Hazard statements**
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ALCON COPPER SUPER LEAK COOLING SYSTEM

Creation date	24th November 2020	Version	3.0
Revision date	21st November 2025		

H412

Harmful to aquatic life with long lasting effects.

Precautionary statements

P101

If medical advice is needed, have product container or label at hand.

P102

Keep out of reach of children.

P280

Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P305+P351+P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310

Immediately call a doctor.

P333+P313

If skin irritation or rash occurs: Get medical advice/attention.

P362+P364

Take off contaminated clothing and wash it before reuse.

P501

Dispose of contents/container to by handing over to the person authorized to dispose of waste or by returning to the supplier.

Supplemental information

EUH071

Corrosive to the respiratory tract.

Requirements for child-resistant fastenings and tactile warning of danger

Container must carry a tactile warning of danger. Container must be fitted with child-resistant fastening.

2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended. Does not contain any PMT or vPvM components.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
CAS: 1344-09-8 EC: 215-687-4	SODIUM SILICATE SOLUTION EXTRA PURE	80-100	Skin Corr. 1, H314 STOT SE 3, H335	
CAS: 151-21-3 EC: 205-788-1	Sodium dodecyl sulphate	0.21-0.315	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 3, H412 Specific concentration limit: Eye Irrit. 2, H319: 10 % ≤ C < 20 % Eye Dam. 1, H318: C ≥ 20 %	
Index: 029-026-00-0 CAS: 7440-50-8 EC: 231-159-6	copper	0.1-0.3	Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=1)	2

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ALCON COPPER SUPER LEAK COOLING SYSTEM

Creation date 24th November 2020 Version 3.0
 Revision date 21st November 2025

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 613-167-00-5 CAS: 55965-84-9	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	≤0.015	Acute Tox. 3, H301 Acute Tox. 2, H310+H330 Skin Corr. 1C, H314 Skin Sens. 1A, H317 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100) EUH071 Specific concentration limit: Eye Irrit. 2, H319: $0.06 \% \leq C < 0.6 \%$ Skin Sens. 1A, H317: $C \geq 0.0015 \%$ Skin Irrit. 2, H315: $0.06 \% \leq C < 0.6 \%$ Skin Corr. 1C, H314: $C \geq 0.6 \%$ Eye Dam. 1, H318: $C \geq 0.6 \%$	1
CAS: 57-11-4 EC: 200-313-4	Stearic acid	≤0.003	not classified as dangerous	

Notes

- Note B: Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis.*
- A substance for which exposure limits are set.*

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet. If unconscious, put the person in the stabilized (recovery) position on his side with his head slightly bent backwards and make sure that airways are free; never induce vomiting. If the person vomits by himself, make sure that the vomit is not inhaled. In life threatening conditions first of all provide resuscitation of the affected person and ensure medical assistance. Respiratory arrest - provide artificial respiration immediately. Cardiac arrest - provide indirect cardiac massage immediately.

If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Take care of your own safety, do not let the affected person walk! Beware of the contaminated clothes. Depending on the situation, call the medical rescue service and ensure medical treatment considering the frequent need of further observation for at least 24 hours.

If on skin

Remove contaminated clothes. Take off any rings, watches, bracelets before or during washing if worn in the contaminated areas of the skin. Rinse contaminated areas with a flow of water, lukewarm at best, for 10-30 minutes; do not use any brush, soap or neutralizers. Depending on the situation, call the medical rescue service and always ensure medical treatment.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. No neutralization should be performed in any case! Rinsing should be continued for 10-30 minutes from the inner to the outer eye corner to make sure that the other eye is not involved. Depending on the situation, call medical rescue service or ensure medical treatment as promptly as possible. Everyone must be referred for treatment even if affected only a little.

If swallowed

RINSE THE MOUTH WITH WATER IMMEDIATELY AND LET THE PERSON DRINK 0.2-0.5 l of cold water to reduce the heating effect of the corrosive substance. Consuming larger amounts of liquid is not advisable as it may induce vomiting and potential inhaling of the corrosive substances in the lungs. The affected person must not be forced to drink, particularly if already feeling pain in the mouth or throat. In this case let the affected person only rinse the mouth with water. DO NOT PROVIDE ACTIVATED CARBON! Depending on the situation, call medical rescue service or ensure medical treatment as promptly as possible.

ALCON COPPER SUPER LEAK COOLING SYSTEM

Creation date	24th November 2020	Version	3.0
Revision date	21st November 2025		

4.2. Most important symptoms and effects, both acute and delayed**If inhaled**

Inhaling vapours can cause corrosion of the breathing system. May cause respiratory irritation.

If on skin

Causes severe skin burns. May cause an allergic skin reaction.

If in eyes

Causes serious eye damage.

If swallowed

Corrosion of the digestion system can occur.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

Unsuitable extinguishing media

Water - full jet.

5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes.

6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

6.4. Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Do not inhale mist/vapours/spray. Prevent contact with skin and eyes. Contaminated work clothing should not be allowed out of the workplace. Wash hands and exposed parts of the body thoroughly after handling. Use only outdoors or in a well-ventilated area. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection. Avoid release to the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Store locked up. Keep container tightly closed.

7.3. Specific end use(s)

not available

ALCON COPPER SUPER LEAK COOLING SYSTEM

Creation date	24th November 2020	Version	3.0
Revision date	21st November 2025		

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

The mixture contains no substances for which occupational exposure limits are set.

Turkey

Substance name (component)	Type	Value
copper (CAS: 7440-50-8)	TWA (8 hours)	0,1 mg/m ³

Notes

As Cu.

8.2. Exposure controls

Take off contaminated clothing and wash before reuse. Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. If exposure limits cannot be observed in this mode, suitable protection of airways must be used. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

Eye/face protection



Protective goggles or face shield (based on the nature of the work performed).

Skin protection



Hand protection: Protective gloves resistant to the product. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. When selecting gloves, consider the properties of the product and the duration of exposure. Replace gloves at the first signs of wear or damage. Other protection: protective workwear. Contaminated skin should be washed thoroughly.

Glove material	Thickness	Breakthrough time	Class	Exposure time
Nitrile (NBR)	≥ 0.3 mm	>30 min	2	Short-term
Nitrile (NBR)	≥ 0.7 mm	>480 min	6	Repeated, Long-term

Respiratory protection



Mask with a filter in a poorly ventilated environment.

Thermal hazard

Not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	liquid
Colour	copper

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ALCON COPPER SUPER LEAK COOLING SYSTEM

Creation date	24th November 2020	Version	3.0
Revision date	21st November 2025		

Odour	Characteristic
Odour threshold	No data available
Melting point/freezing point	data not available
Boiling point or initial boiling point and boiling range	data not available
Flammability	data not available
Lower and upper explosion limit	data not available
Flash point	data not available
Auto-ignition temperature	data not available
Decomposition temperature	data not available
pH	11-12 (undiluted)
Kinematic viscosity	data not available
Viscosity	No data available
Solubility in water	No data available
Solubility in fats	No data available
Partition coefficient n-octanol/water (log value)	No data available
Vapour pressure	No data available
Density and/or relative density	
Density	1.5-1.6 g/cm ³
Relative density	No data available
Relative vapour density	data not available
Particle characteristics	data not available
9.2. Other information	
Oxidising properties	No data available
Vapour density	No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Unknown.

10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost.

10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

No toxicological data is available for the mixture.

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ALCON COPPER SUPER LEAK COOLING SYSTEM

Creation date 24th November 2020 Version 3.0
 Revision date 21st November 2025

Acute toxicity

Based on the available data, the criteria for classification of the mixture are not met.

ALCON COPPER SUPER LEAK COOLING SYSTEM							
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination
Oral	ATE		128205 mg/kg				Calculation of value
Dermal	ATE		333333 mg/kg				Calculation of value
Inhalation (vapor)	ATE		3333 mg/l				Calculation of value

copper							
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination
Dermal	LD ₅₀	OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal), Guideline: EPA OTS 798.1100 (Acute Dermal Toxicity), Guideline: other:MAFF 4200 (1985)	>2000 mg/kg		Rat (None)		
Inhalation	LC ₅₀	OECD Guideline 436 (Acute Inhalation Toxicity: Acute Toxic Class Method)	>5.11 mg/l		Rat (None)		

SODIUM SILICATE SOLUTION EXTRA PURE							
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination
Dermal	LD ₅₀	EPA OPPTS 870.1200 (Acute Dermal Toxicity)	>5000 mg/kg		Rat (None)		
Inhalation	LC ₅₀	EPA OPPTS 870.1300 (Acute inhalation toxicity)	>2.06 mg/l		Rat (None)		

Sodium dodecyl sulphate							
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination
Dermal	LD ₅₀	OECD Guideline 402 (Acute Dermal Toxicity)	>2000 mg/kg		Rat (None)		



SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ALCON COPPER SUPER LEAK COOLING SYSTEM

Creation date 24th November 2020 Version 3.0
Revision date 21st November 2025

Stearic acid							
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination
Dermal	LD ₅₀	OECD Guideline 434 (Acute Dermal Toxicity - Fixed Dose Procedure)	>2000 mg/kg		Rabbit (None)		
Inhalation	LC ₅₀		>0.1621 mg/l		Rat (None)		

Skin corrosion/irritation

Causes severe skin burns and eye damage. Data for the components of the mixture are not available.

Serious eye damage/irritation

Causes severe skin burns and eye damage. Causes serious eye damage. Data for the components of the mixture are not available.

Respiratory or skin sensitisation

May cause an allergic skin reaction. Data for the components of the mixture are not available.

Germ cell mutagenicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Carcinogenicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Reproductive toxicity

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

SODIUM SILICATE SOLUTION EXTRA PURE						
Effect	Parameter	Value	Exposure time	Result	Species	Sex
	NOAEL	>159 mg/kg			Rat (None)	F

Toxicity for specific target organ - single exposure

May cause respiratory irritation. Data for the components of the mixture are not available.

Toxicity for specific target organ - repeated exposure

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ALCON COPPER SUPER LEAK COOLING SYSTEM

Creation date 24th November 2020
 Revision date 21st November 2025

Version 3.0

Repeated dose toxicity

Stearic acid							
Route of exposure	Parameter	Result	Method	Value	Exposure time	Species	Sex
Oral	NOAEL		OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)	1000 mg/kg	90 days	Rat (None)	

Aspiration hazard

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

11.2. Information on other hazards

Endocrine disrupting properties

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any components that may cause endocrine disruption for humans.

Other information

not available

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

Acute toxicity

ALCON COPPER SUPER LEAK COOLING SYSTEM				
Parameter	Value	Exposure time	Species	Environment
EC ₅₀	53 mg/l	72 hours	Algae (Desmodesmus subspicatus (previous name: Scenedesmus subspicatus))	

SODIUM SILICATE SOLUTION EXTRA PURE				
Parameter	Value	Exposure time	Species	Environment
LC ₅₀	1108 mg/l		Fish (Danio rerio (previous name: Brachydanio rerio))	
EC ₅₀	1700 mg/l		Daphnia (Daphnia magna)	
EC ₅₀	207 mg/l	72 hours	Algae (Desmodesmus subspicatus (previous name: Scenedesmus subspicatus))	

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ALCON COPPER SUPER LEAK COOLING SYSTEM

Creation date 24th November 2020 Version 3.0
 Revision date 21st November 2025

SODIUM SILICATE SOLUTION EXTRA PURE

Parameter	Value	Exposure time	Species	Environment
EC ₅₀	> 345.4 mg/l	72 hours	Algae (Desmodesmus subspicatus (previous name: Scenedesmus subspicatus))	

Sodium dodecyl sulphate

Parameter	Value	Exposure time	Species	Environment
LC ₅₀	29 mg/l		Fish (Pimephales promelas)	
EC ₅₀	11.1 mg/l		Crustaceans (Pseudosida ramosa)	
EC ₅₀	> 120 mg/l	72 hours	Algae (Desmodesmus subspicatus (previous name: Scenedesmus subspicatus))	

Stearic acid

Parameter	Value	Exposure time	Species	Environment
EC ₅₀	> 4.8 mg/l		Daphnia (Daphnia magna)	
EC ₅₀	> 0.9 mg/l	72 hours	Algae (Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum))	

Chronic toxicity

ALCON COPPER SUPER LEAK COOLING SYSTEM

Parameter	Value	Exposure time	Species	Environment
NOEC _{chronic} fish	≥ 1.357 mg/l	42 days	Fish (Pimephales promelas)	

Stearic acid

Parameter	Value	Exposure time	Species	Environment
LOEC(chronic)	> 0.22 mg/l	21 days	Daphnia (Daphnia magna)	
NOEC(chronic)	> 0.22 mg/l	21 days	Daphnia (Daphnia magna)	

12.2. Persistence and degradability

No data are available for either the mixture or the components.

12.3. Bioaccumulative potential

No data are available for either the mixture or the components.

12.4. Mobility in soil

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any PMT or vPvM components.

12.5. Results of PBT and vPvB assessment

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any PBT or vPvB components.

12.6. Endocrine disrupting properties

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any components that may cause endocrine disruption in the environment.

12.7. Other adverse effects

Not available.

ALCON COPPER SUPER LEAK COOLING SYSTEM

Creation date	24th November 2020	Version	3.0
Revision date	21st November 2025		

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

SECTION 14: Transport information

14.1. UN number or ID number

UN 3266

14.2. UN proper shipping name

CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S.

14.3. Transport hazard class(es)

8 Corrosive substances

14.4. Packing group

III

14.5. Environmental hazards

not relevant

14.6. Special precautions for user

Reference in the Sections 4 to 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant


Additional information

Hazard identification No.

UN number

Classification code

Safety signs



C5

8



ALCON COPPER SUPER LEAK COOLING SYSTEM

Creation date	24th November 2020	Version	3.0
Revision date	21st November 2025		

Road transport - ADR

Special provisions	274
Limited quantities	5 L
Excepted quantities	E1

Packaging

Packing instructions	P001, IBC03, LP01, R001
Mixed packing provisions	MP19

Portable tanks and bulk containers

Guidelines	T7
Special provisions	TP1, TP28

ADR tank

Tank code	L4BN
Special provisions	TU42
Vehicles for tank carriage	AT
Transport category	3
Tunnel restriction code	(E)

Special provision for packages

V12

Railway transport - RID

Special provisions	274
--------------------	-----

Packaging

Packing instructions	P001, IBC03, LP01, R001
Mixed packing provisions	MP19

Portable tanks and bulk containers

Guidelines	T7
Special provisions	TP1, TP28

RID Tanks

Tank code	L4BN
Special provisions	TU42
Transport category	3

Special provision for packages

W12

Air transport - ICAO/IATA

Packaging instructions for limited amount	Y841
Packaging instructions passenger	852
Cargo packaging instructions	856

Marine transport - IMDG

EmS (emergency plan)	F-A, S-B
----------------------	----------

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

not available

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ALCON COPPER SUPER LEAK COOLING SYSTEM

Creation date	24th November 2020	Version	3.0
Revision date	21st November 2025		

SECTION 16: Other information

A list of standard risk phrases used in the safety data sheet

EUH071	Corrosive to the respiratory tract.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310+H330	Fatal in contact with skin or if inhaled.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Guidelines for safe handling used in the safety data sheet

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a doctor.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P501	Dispose of contents/container to by handing over to the person authorized to dispose of waste or by returning to the supplier.

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

Acute Tox.	Acute toxicity
ADR	Agreement concerning the international carriage of dangerous goods by road
Aquatic Acute	Hazardous to the aquatic environment
Aquatic Chronic	Hazardous to the aquatic environment (chronic)
ATE	Acute toxicity estimate
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
EC	Identification code for each substance listed in EINECS
EC ₅₀	Concentration of a substance when it is affected 50 % of the population
EINECS	European Inventory of Existing Commercial Chemical Substances
EmS	Emergency Response Procedures for Ships Carrying Dangerous Goods
EU	European Union
EuPCS	European Product Categorisation System
Eye Dam.	Serious eye damage
Eye Irrit.	Eye irritation
IATA	International Air Transport Association

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ALCON COPPER SUPER LEAK COOLING SYSTEM

Creation date	24th November 2020	Version	3.0
Revision date	21st November 2025		

IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization
IUPAC	International Union of Pure and Applied Chemistry
LC ₅₀	Lethal concentration of a substance in which it can be expected death of 50% of the population
LD ₅₀	Lethal dose of a substance in which it can be expected death of 50% of the population
log K _{ow}	Octanol-water partition coefficient
NOAEL	No observed adverse effect level
NOEC	No observed effect concentration
OEL	Occupational Exposure Limits
PBT	Persistent, bioaccumulative and toxic
PMT	Persistent, mobile and toxic
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulation concerning the International Carriage of Dangerous Goods by Rail
Skin Corr.	Skin corrosion
Skin Irrit.	Skin irritation
Skin Sens.	Skin sensitization
STOT SE	Specific target organ toxicity - single exposure
UN number	Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB	Substances of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very persistent and very bioaccumulative
vPvM	Very persistent and very mobile

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended.
REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

More information

Classification procedure - calculation method.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.