

ALCON DIESEL FUEL ANTI-FREEZE

Creation date	18th February 2020	Version	2.0
Revision date	23rd December 2025		

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. **Product identifier** ALCON DIESEL FUEL ANTI-FREEZE
Substance / mixture mixture
Number M-9607
- 1.2. **Relevant identified uses of the substance or mixture and uses advised against**
Mixture's intended use
This product protects fluency of diesel fuel in a cold weather by under control to occurrence of paraffin crystal on fuel and also avoid congesting of filters. Protects core spray system from corrosion and rust. Facilitates the starting of the engine.
Mixture uses advised against
The product should not be used in ways other than those referred in Section 1.
- 1.3. **Details of the supplier of the safety data sheet**
Manufacturer
Name or trade name ALCON ENDÜSTRİYEL ÜRÜNLER SAN. VE TİC. LTD. ŞTİ.
Address SOĞANLIK YENİ MAH. ALİAĞA SOK. NO:8 DAİRE:37 Bumerang
Kartal Rezidans Kartal, İstanbul, 34880
Turkey
Phone +90 216 661 00 90
Email alcon@alcon.com.tr
Web address www.alcon.com.tr
- 1.4. **Emergency telephone number**
European emergency number: 112

SECTION 2: Hazards identification

- 2.1. **Classification of the substance or mixture**
Classification of the mixture in accordance with Regulation (EC) No 1272/2008
The mixture is classified as dangerous.
- Flam. Liq. 2, H225
Asp. Tox. 1, H304
Eye Irrit. 2, H319
Muta. 1B, H340
Carc. 1B, H350
STOT RE 1, H372 (central nervous system)
- Most serious adverse physico-chemical effects**
Highly flammable liquid and vapour.
- Most serious adverse effects on human health and the environment**
May be fatal if swallowed and enters airways. Causes serious eye irritation. May cause genetic defects. May cause cancer. Causes damage to the central nervous system through prolonged or repeated exposure.
- 2.2. **Label elements**
Hazard pictogram
- 
- Signal word**
Danger
- Hazardous substances**
stoddard solvent
butanone
propan-2-ol

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ALCON DIESEL FUEL ANTI-FREEZE

Creation date	18th February 2020	Version	2.0
Revision date	23rd December 2025		

Hazard statements

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H340	May cause genetic defects.
H350	May cause cancer.
H372	Causes damage to the central nervous system through prolonged or repeated exposure.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear eye protection/protective gloves/protective clothing.
P301+P310	IF SWALLOWED: Immediately call a doctor.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P331	Do NOT induce vomiting.
P405	Store locked up.
P501	Dispose of contents/container to by handing over to the person authorized to dispose of waste or by returning to the supplier.

Requirements for child-resistant fastenings and tactile warning of danger

Container must carry a tactile warning of danger. Container must be fitted with child-resistant fastening.

2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended. Does not contain any PMT or vPvM components.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

Mixture.

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 649-345-00-4 CAS: 8052-41-3 EC: 232-489-3	stoddard solvent	80-90	Asp. Tox. 1, H304 Muta. 1B, H340 Carc. 1B, H350 STOT RE 1, H372 (central nervous system)	1, 2, 3
Index: 606-002-00-3 CAS: 78-93-3 EC: 201-159-0	butanone	3-5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066	2, 4
Index: 603-117-00-0 CAS: 67-63-0 EC: 200-661-7	propan-2-ol	1-5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	2

ALCON DIESEL FUEL ANTI-FREEZE

Creation date	18th February 2020	Version	2.0
Revision date	23rd December 2025		

Notes

- 1 *Note P: The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0,1 % w/w benzene (Einecs No 200-753-7), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 shall apply.*
- 2 *A substance for which exposure limits are set.*
- 3 *The use of the substance is restricted by Annex XVII of REACH Regulation*
- 4 *Drug precursor*

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures**

Do not perform artificial respiration without self-protection (e.g. a mask). Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet. If unconscious, put the person in the stabilized (recovery) position on his side with his head slightly bent backwards and make sure that airways are free; never induce vomiting. If the person vomits by himself, make sure that the vomit is not inhaled. In life threatening conditions first of all provide resuscitation of the affected person and ensure medical assistance. Respiratory arrest - provide artificial respiration immediately. Cardiac arrest - provide indirect cardiac massage immediately.

If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Take care of your own safety, do not let the affected person walk! Beware of the contaminated clothes. Depending on the situation, call the medical rescue service and ensure medical treatment considering the frequent need of further observation for at least 24 hours.

If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible. Soap, soap solution or shampoo should be used if there is no skin injury. Provide medical treatment if skin irritation persists. Rinse skin with water or shower.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Rinsing should continue at least for 10 minutes. Provide medical treatment, specialized if possible.

If swallowed

If the affected person vomits, make sure to prevent inhalation of the vomit (as there is a danger of lung damage after inhalation of these liquids in the airways also in infinitesimal amount). Provide medical treatment considering the frequent need of further observation for at least 24 hours. Bring an original container with the label and the Safety Data Sheet of the given substance as appropriate.

4.2. Most important symptoms and effects, both acute and delayed**If inhaled**

Cough, headache.

If on skin

Not expected.

If in eyes

Causes serious eye irritation.

If swallowed

Irritation, nausea.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

Unsuitable extinguishing media

Water - full jet.

ALCON DIESEL FUEL ANTI-FREEZE

Creation date	18th February 2020	Version	2.0
Revision date	23rd December 2025		

5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Provide sufficient ventilation. Highly flammable liquid and vapour. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes.

6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

6.4. Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes. No smoking. Obtain special instructions before use. Wash hands and exposed parts of the body thoroughly after handling. Do not eat, drink or smoke when using this product. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Take action to prevent static discharges.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Do not expose to sunlight. Store locked up. Keep container tightly closed. Keep cool.

The specific requirements or rules relating to the substance/mixture

Solvent vapours are heavier than air and accumulate especially near the floor where they may form an explosive mixture with the air.

7.3. Specific end use(s)

not available

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

The mixture contains substances for which occupational exposure limits are set.

European Union**Commission Directive 2000/39/EC**

Substance name (component)	Type	Value
butanone (CAS: 78-93-3)	OEL 8 hours	600 mg/m ³
	OEL 8 hours	200 ppm
	OEL 15 minutes	900 mg/m ³
	OEL 15 minutes	300 ppm

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ALCON DIESEL FUEL ANTI-FREEZE

Creation date 18th February 2020 Version 2.0
 Revision date 23rd December 2025

Turkey

Substance name (component)	Type	Value
stoddard solvent (CAS: 8052-41-3)	TWA (8 hours)	2900 mg/m ³
	TWA (8 hours)	500 ppm
butanone (CAS: 78-93-3)	TWA (8 hours)	600 mg/m ³
	TWA (8 hours)	200 ppm
	STEL (15 min.)	900 mg/m ³
	STEL (15 min.)	300 ppm
propan-2-ol (CAS: 67-63-0)	TWA (8 hours)	980 mg/m ³
	TWA (8 hours)	400 ppm

8.2. Exposure controls

Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

Eye/face protection



Protective goggles.

Skin protection



Hand protection: Protective gloves resistant to the product. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Other protection: Protective antistatic clothing made of natural fibres (cotton) or synthetic fibres resistant to elevated temperatures. Antistatic footwear. Contaminated skin should be washed thoroughly.

Glove material	Thickness	Breakthrough time	Class
Nitrile (NBR)	≥ 0.4 mm	>480 min	6

Respiratory protection



Mask with a filter against organic vapours in a poorly ventilated environment.

Thermal hazard

Not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state liquid

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ALCON DIESEL FUEL ANTI-FREEZE

Creation date	18th February 2020	Version	2.0
Revision date	23rd December 2025		

Colour	blue
Odour	Characteristic
Melting point/freezing point	data not available
Boiling point or initial boiling point and boiling range	82.5 °C
Flammability	data not available
Lower and upper explosion limit	data not available
Flash point	data not available
Auto-ignition temperature	data not available
Decomposition temperature	data not available
pH	4 (undiluted)
Kinematic viscosity	data not available
Solubility in water	insoluble in water.
Partition coefficient n-octanol/water (log value)	data not available
Vapour pressure	data not available
Density and/or relative density	
Density	0.75-0.8 g/cm ³
Relative vapour density	data not available
Particle characteristics	data not available

9.2. Other information

not available

SECTION 10: Stability and reactivity**10.1. Reactivity**

Highly flammable liquid and vapour.

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Unknown.

10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost.

10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Hazardous substances in concentrations exceeding exposure limits may cause acute inhalation poisoning, depending on the concentration and duration of exposure. No toxicological data is available for the mixture.

Acute toxicity

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

propan-2-ol						
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex
Oral	LD ₅₀	OECD Guideline 401 (Acute Oral Toxicity)	5840 mg/kg		Rat	

ALCON DIESEL FUEL ANTI-FREEZE

Creation date	18th February 2020	Version	2.0
Revision date	23rd December 2025		

Skin corrosion/irritation

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Serious eye damage/irritation

Causes serious eye irritation. Data for the components of the mixture are not available.

Respiratory or skin sensitisation

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Germ cell mutagenicity

May cause genetic defects. Data for the components of the mixture are not available.

Carcinogenicity

May cause cancer. Data for the components of the mixture are not available.

Reproductive toxicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Toxicity for specific target organ - single exposure

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Toxicity for specific target organ - repeated exposure

Causes damage to the central nervous system through prolonged or repeated exposure. Data for the components of the mixture are not available.

Aspiration hazard

May be fatal if swallowed and enters airways. Data for the components of the mixture are not available.

11.2. Information on other hazards**Endocrine disrupting properties**

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any components that may cause endocrine disruption for humans.

Other information

not available

SECTION 12: Ecological information**12.1. Toxicity**

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

Acute toxicity

butanone				
Parameter	Value	Exposure time	Species	Environment
LC ₅₀	2993 mg/l		Fish (Pimephales promelas)	
EC ₅₀	308 mg/l		Daphnia (Daphnia magna)	
EC ₅₀	1972 mg/l		Algae (Pseudokirchneriella subcapitata)	

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ALCON DIESEL FUEL ANTI-FREEZE

Creation date 18th February 2020 Version 2.0
 Revision date 23rd December 2025

butanone				
Parameter	Value	Exposure time	Species	Environment
EC ₅₀	2029 mg/l		Algae (Pseudokirchneriella subcapitata)	

propan-2-ol				
Parameter	Value	Exposure time	Species	Environment
LC ₅₀	10000 mg/l		Fish (Pimephales promelas)	
LC ₅₀	9640 mg/l		Fish (Pimephales promelas)	

12.2. Persistence and degradability

No data are available for either the mixture or the components.

12.3. Bioaccumulative potential

No data are available for either the mixture or the components.

12.4. Mobility in soil

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any PMT or vPvM components.

12.5. Results of PBT and vPvB assessment

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any PBT or vPvB components.

12.6. Endocrine disrupting properties

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any components that may cause endocrine disruption in the environment.

12.7. Other adverse effects

Not available.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

SECTION 14: Transport information**14.1. UN number or ID number**

UN 3295

14.2. UN proper shipping name

HYDROCARBONS, LIQUID, N.O.S.

14.3. Transport hazard class(es)

3 Flammable liquids

14.4. Packing group

II

14.5. Environmental hazards

not relevant

14.6. Special precautions for user

Reference in the Sections 4 to 8.

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ALCON DIESEL FUEL ANTI-FREEZE

Creation date	18th February 2020	Version	2.0
Revision date	23rd December 2025		

14.7. Maritime transport in bulk according to IMO instruments

not relevant

Additional information

Hazard identification No.

33

UN number

3295

Classification code

F1

Safety signs

3



Road transport - ADR

Special provisions

640C

Limited quantities

1 L

Excepted quantities

E2

Packaging

Packing instructions

P001

Mixed packing provisions

MP19

Portable tanks and bulk containers

Guidelines

T7

Special provisions

TP1, TP8, TP28

ADR tank

Tank code

L1,5BN

Vehicles for tank carriage

FL

Transport category

2

Tunnel restriction code

(D/E)

Special provision for

operation

S2, S20

Railway transport - RID

Special provisions

640C

Packaging

Packing instructions

P001

Mixed packing provisions

MP19

Portable tanks and bulk containers

Guidelines

T7

Special provisions

TP1, TP8, TP28

RID Tanks

Tank code

L1,5BN

Transport category

2

Air transport - ICAO/IATA

Packaging instructions for limited amount

Y344

Packaging instructions passenger

355

Cargo packaging instructions

366

Marine transport - IMDG

EmS (emergency plan)

F-E, S-D

MFAG

310

ALCON DIESEL FUEL ANTI-FREEZE

Creation date	18th February 2020	Version	2.0
Revision date	23rd December 2025		

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

Restrictions pursuant to Annex XVII of Regulation (EC) No. 1907/2006 (REACH), as amended

stoddard solvent

Restriction	Conditions of restriction
28	1. Shall not be placed on the market, or used, — as substances, — as constituents of other substances, or, — in mixtures, for supply to the general public when the individual concentration in the substance or mixture is equal to or greater than: — either the relevant specific concentration limit specified in Part 3 of Annex VI to Regulation (EC) No 1272/2008, - or, — the relevant generic concentration limit specified in Part 3 of Annex I of Regulation (EC) No 1272/2008. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that the packaging of such substances and mixtures is marked visibly, legibly and indelibly as follows: “Restricted to professional users”. 2. By way of derogation, paragraph 1 shall not apply to: (a) medicinal or veterinary products as defined by Directive 2001/82/EC and Directive 2001/83/EC; (b) cosmetic products as defined by Directive 76/768/EEC; (c) the following fuels and oil products: — motor fuels which are covered by Directive 98/70/EC, — mineral oil products intended for use as fuel in mobile or fixed combustion plants, — fuels sold in closed systems (e.g. liquid gas bottles); (d) artists' paints covered by Regulation (EC) No 1272/2008; (e) the substances listed in Appendix 11, column 1, for the applications or uses listed in Appendix 11, column 2. Where a date is specified in column 2 of Appendix 11, the derogation shall apply until the said date. (f) devices covered by Regulation (EU) 2017/745.

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ALCON DIESEL FUEL ANTI-FREEZE

Creation date	18th February 2020	Version	2.0
Revision date	23rd December 2025		

stoddard solvent

Restriction	Conditions of restriction
29	1. Shall not be placed on the market, or used, — as substances, — as constituents of other substances, or, — in mixtures, for supply to the general public when the individual concentration in the substance or mixture is equal to or greater than: — either the relevant specific concentration limit specified in Part 3 of Annex VI to Regulation (EC) No 1272/2008, - or, — the relevant generic concentration limit specified in Part 3 of Annex I of Regulation (EC) No 1272/2008. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that the packaging of such substances and mixtures is marked visibly, legibly and indelibly as follows: “Restricted to professional users”. 2. By way of derogation, paragraph 1 shall not apply to: (a) medicinal or veterinary products as defined by Directive 2001/82/EC and Directive 2001/83/EC; (b) cosmetic products as defined by Directive 76/768/EEC; (c) the following fuels and oil products: — motor fuels which are covered by Directive 98/70/EC, — mineral oil products intended for use as fuel in mobile or fixed combustion plants, — fuels sold in closed systems (e.g. liquid gas bottles); (d) artists' paints covered by Regulation (EC) No 1272/2008; (e) the substances listed in Appendix 11, column 1, for the applications or uses listed in Appendix 11, column 2. Where a date is specified in column 2 of Appendix 11, the derogation shall apply until the said date. (f) devices covered by Regulation (EU) 2017/745.

15.2. Chemical safety assessment

not available

SECTION 16: Other information

A list of standard risk phrases used in the safety data sheet

EUH066	Repeated exposure may cause skin dryness or cracking.
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H350	May cause cancer.
H372	Causes damage to the central nervous system through prolonged or repeated exposure.

Guidelines for safe handling used in the safety data sheet

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear eye protection/protective gloves/protective clothing.
P301+P310	IF SWALLOWED: Immediately call a doctor.
P308+P313	IF exposed or concerned: Get medical advice/attention.

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ALCON DIESEL FUEL ANTI-FREEZE

Creation date	18th February 2020	Version	2.0
Revision date	23rd December 2025		

P331	Do NOT induce vomiting.
P405	Store locked up.
P501	Dispose of contents/container to by handing over to the person authorized to dispose of waste or by returning to the supplier.

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

ADR	Agreement concerning the international carriage of dangerous goods by road
Asp. Tox.	Aspiration hazard
BCF	Bioconcentration Factor
Carc.	Carcinogenicity
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
EC	Identification code for each substance listed in EINECS
EC ₅₀	Concentration of a substance when it is affected 50 % of the population
EINECS	European Inventory of Existing Commercial Chemical Substances
EmS	Emergency Response Procedures for Ships Carrying Dangerous Goods
EU	European Union
EuPCS	European Product Categorisation System
Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquid
IATA	International Air Transport Association
IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization
IUPAC	International Union of Pure and Applied Chemistry
LC ₅₀	Lethal concentration of a substance in which it can be expected death of 50% of the population
LD ₅₀	Lethal dose of a substance in which it can be expected death of 50% of the population
log Kow	Octanol-water partition coefficient
Muta.	Germ cell mutagenicity
OEL	Occupational Exposure Limits
PBT	Persistent, bioaccumulative and toxic
PMT	Persistent, mobile and toxic
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulation concerning the International Carriage of Dangerous Goods by Rail
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure
UN number	Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB	Substances of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very persistent and very bioaccumulative
vPvM	Very persistent and very mobile

Training guidelines



SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ALCON DIESEL FUEL ANTI-FREEZE

Creation date	18th February 2020	Version	2.0
Revision date	23rd December 2025		

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended.
REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

More information

Classification procedure - calculation method.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.