

ALCON (TI) PLASTIC METAL BOND EPOXY & TITANIUM (PUTTY) - CATALYST

Creation date	01st March 2021	Version	3.0
Revision date	16th December 2025		

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier**
ALCON (TI) PLASTIC METAL BOND EPOXY & TITANIUM (PUTTY) - CATALYST
Substance / mixture mixture
Number M-2234
- 1.2. Relevant identified uses of the substance or mixture and uses advised against**
Mixture's intended use
Catalyst
Mixture uses advised against
The product should not be used in ways other than those referred in Section 1.
- 1.3. Details of the supplier of the safety data sheet**
Manufacturer
Name or trade name ALCON ENDÜSTRİYEL ÜRÜNLER SAN. VE TİC. LTD. ŞTİ.
Address SOĞANLIK YENİ MAH. ALİAĞA SOK. NO:8 DAİRE:37 Bumerang
Kartal Rezidans Kartal, İstanbul, 34880
Turkey
Phone +90 216 661 00 90
Email alcon@alcon.com.tr
Web address www.alcon.com.tr
- 1.4. Emergency telephone number**
European emergency number: 112

SECTION 2: Hazards identification

- 2.1. Classification of the substance or mixture**
Classification of the mixture in accordance with Regulation (EC) No 1272/2008
The mixture is classified as dangerous.

Acute Tox. 4, H302
Skin Corr. 1, H314
Skin Sens. 1B, H317
Eye Dam. 1, H318
Most serious adverse effects on human health and the environment
Harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye damage.
- 2.2. Label elements**
Hazard pictogram

Signal word
Danger
Hazardous substances
Polyaminoamide hardener
benzyl alcohol
Phenolpolymer polyamine
titanium dioxide
Hazard statements
H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.

ALCON (TI) PLASTIC METAL BOND EPOXY & TITANIUM (PUTTY) - CATALYST

Creation date 01st March 2021 Version 3.0
Revision date 16th December 2025

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P264 Wash face, hands and exposed parts of the body thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P312 IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell.
P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a doctor.
P501 Dispose of contents/container to by handing over to the person authorized to dispose of waste or by returning to the supplier.

Supplemental information

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Requirements for child-resistant fastenings and tactile warning of danger

Container must carry a tactile warning of danger. Container must be fitted with child-resistant fastening.

2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended. Does not contain any PMT or vPvM components.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
	Polyaminoamide hardener	50-60	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319	
Index: 603-057-00-5 CAS: 100-51-6 EC: 202-859-9	benzyl alcohol	20-30	Acute Tox. 4, H302 Skin Sens. 1B, H317 Eye Irrit. 2, H319 Specific concentration limit: ATE Oral = 1200 mg/kg bw	
	Phenolpolymer polyamine	10-20	Acute Tox. 4, H302+H332 Skin Corr. 1, H314 Skin Sens. 1, H317 Aquatic Chronic 3, H412	
Index: 022-006-00-2 CAS: 13463-67-7 EC: 236-675-5	titanium dioxide	5-10	Carc. 2, H351 (inhalation) EUH208	1, 2, 3
CAS: 7631-86-9 EC: 231-545-4	Silicon dioxide	5-10	not classified as dangerous EUH208	

ALCON (TI) PLASTIC METAL BOND EPOXY & TITANIUM (PUTTY) - CATALYST

Creation date	01st March 2021	Version	3.0
Revision date	16th December 2025		

Notes

- Note V: If the substance is to be placed on the market as fibres (with diameter < 3 µm, length > 5 µm and aspect ratio ≥ 3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied.*
- Note W: It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung.*

This note aims to describe the particular toxicity of the substance; it does not constitute a criterion for classification according to this Regulation.

- Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 µm.*

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures**

Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet. If unconscious, put the person in the stabilized (recovery) position on his side with his head slightly bent backwards and make sure that airways are free; never induce vomiting. If the person vomits by himself, make sure that the vomit is not inhaled. In life threatening conditions first of all provide resuscitation of the affected person and ensure medical assistance. Respiratory arrest - provide artificial respiration immediately. Cardiac arrest - provide indirect cardiac massage immediately.

If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Take care of your own safety, do not let the affected person walk! Beware of the contaminated clothes. Depending on the situation, call the medical rescue service and ensure medical treatment considering the frequent need of further observation for at least 24 hours.

If on skin

Remove contaminated clothes. Take off any rings, watches, bracelets before or during washing if worn in the contaminated areas of the skin. Rinse contaminated areas with a flow of water, lukewarm at best, for 10-30 minutes; do not use any brush, soap or neutralizers. Depending on the situation, call the medical rescue service and always ensure medical treatment.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. No neutralization should be performed in any case! Rinsing should be continued for 10-30 minutes from the inner to the outer eye corner to make sure that the other eye is not involved. Depending on the situation, call medical rescue service or ensure medical treatment as promptly as possible. Everyone must be referred for treatment even if affected only a little.

If swallowed

RINSE THE MOUTH WITH WATER IMMEDIATELY AND LET THE PERSON DRINK 0.2-0.5 l of cold water to reduce the heating effect of the corrosive substance. Consuming larger amounts of liquid is not advisable as it may induce vomiting and potential inhaling of the corrosive substances in the lungs. The affected person must not be forced to drink, particularly if already feeling pain in the mouth or throat. In this case let the affected person only rinse the mouth with water. DO NOT PROVIDE ACTIVATED CARBON! Depending on the situation, call medical rescue service or ensure medical treatment as promptly as possible.

4.2. Most important symptoms and effects, both acute and delayed**If inhaled**

Inhaling vapours can cause corrosion of the breathing system.

If on skin

Causes severe skin burns. May cause an allergic skin reaction.

If in eyes

Causes serious eye damage.

If swallowed

Corrosion of the digestion system can occur.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

ALCON (TI) PLASTIC METAL BOND EPOXY & TITANIUM (PUTTY) - CATALYST

Creation date	01st March 2021	Version	3.0
Revision date	16th December 2025		

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

Unsuitable extinguishing media

Water - full jet.

5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes.

6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

6.4. Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Do not inhale mist/vapours/spray. Prevent contact with skin and eyes. Contaminated work clothing should not be allowed out of the workplace. Wash hands and exposed parts of the body thoroughly after handling. Do not eat, drink or smoke when using this product. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Store locked up.

7.3. Specific end use(s)

not available

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

The mixture contains no substances for which occupational exposure limits are set.

ALCON (TI) PLASTIC METAL BOND EPOXY & TITANIUM (PUTTY) - CATALYST

Creation date

01st March 2021

Version

3.0

Revision date

16th December 2025

8.2. Exposure controls

Take off contaminated clothing and wash before reuse. Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

Eye/face protection

Protective goggles or face shield (based on the nature of the work performed).

Skin protection

Hand protection: Protective gloves resistant to the product. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. When selecting gloves, consider the properties of the product and the duration of exposure. Replace gloves at the first signs of wear or damage. Other protection: protective workwear. Contaminated skin should be washed thoroughly.

Glove material	Thickness	Breakthrough time	Class	Exposure time
Nitrile (NBR)	≥ 0.3 mm	>30 min	2	Short-term
Nitrile (NBR)	≥ 0.7 mm	>480 min	6	Repeated, Long-term

Respiratory protection

Mask with a filter in a poorly ventilated environment.

Thermal hazard

Not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state	liquid
Colour	grey
Odour	Characteristic
Melting point/freezing point	data not available
Boiling point or initial boiling point and boiling range	data not available
Flammability	data not available
Lower and upper explosion limit	data not available
Flash point	data not available
Auto-ignition temperature	data not available
Decomposition temperature	data not available
pH	data not available
Kinematic viscosity	data not available
Solubility in water	data not available
Partition coefficient n-octanol/water (log value)	data not available

ALCON (TI) PLASTIC METAL BOND EPOXY & TITANIUM (PUTTY) - CATALYST

Creation date	01st March 2021	Version	3.0
Revision date	16th December 2025		

Vapour pressure	data not available
Density and/or relative density	data not available
Relative vapour density	data not available
Particle characteristics	data not available
Form	liquid - solid: mixture of, paste

9.2. Other information

not available

SECTION 10: Stability and reactivity**10.1. Reactivity**

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Unknown.

10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost.

10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

No toxicological data is available for the mixture.

Acute toxicity

Harmful if swallowed.

ALCON (TI) PLASTIC METAL BOND EPOXY & TITANIUM (PUTTY) - CATALYST							
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination
Oral	ATE		631.6 mg/kg				Calculation of value
Inhalation (vapor)	ATE		84.62 mg/l				Calculation of value

benzyl alcohol							
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination
Oral	ATE		1200 mg/kg bw				

ALCON (TI) PLASTIC METAL BOND EPOXY & TITANIUM (PUTTY) - CATALYST

Creation date

01st March 2021

Version

3.0

Revision date

16th December 2025

titanium dioxide							
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination
Oral	LD ₅₀	OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure), EPA OPPTS 870.1100 (Acute Oral Toxicity)	>5000 mg/kg		Rat (Rattus norvegicus)	F	

Skin corrosion/irritation

Causes severe skin burns and eye damage. Data for the components of the mixture are not available.

Serious eye damage/irritation

Causes severe skin burns and eye damage. Causes serious eye damage. Data for the components of the mixture are not available.

Respiratory or skin sensitisation

May cause an allergic skin reaction. Data for the components of the mixture are not available.

Germ cell mutagenicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Carcinogenicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Reproductive toxicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Toxicity for specific target organ - single exposure

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Toxicity for specific target organ - repeated exposure

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Aspiration hazard

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

11.2. Information on other hazards**Endocrine disrupting properties**

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any components that may cause endocrine disruption for humans.

Other information

not available

ALCON (TI) PLASTIC METAL BOND EPOXY & TITANIUM (PUTTY) - CATALYST

Creation date 01st March 2021 Version 3.0
Revision date 16th December 2025

SECTION 12: Ecological information**12.1. Toxicity**

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

Acute toxicity

titanium dioxide					
Parameter	Value	Exposure time	Species	Environment	Source
LC ₅₀	155 mg/l		Fish		[1]
LC ₅₀	155 mg/l		Fish		[1]
EC ₅₀	19.3 mg/l		Daphnia		[1]
EC ₅₀	27.8 mg/l		Daphnia		[2]
EC ₅₀	>100 mg/l	72 hours	Algae (Pseudokirchneriella subcapitata)		[1]

Chronic toxicity

titanium dioxide				
Parameter	Value	Exposure time	Species	Environment
NOEC(chronic)	2.92 mg/l	21 days	Daphnia	

12.2. Persistence and degradability

No data are available for either the mixture or the components.

12.3. Bioaccumulative potential

No data are available for either the mixture or the components.

12.4. Mobility in soil

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any PMT or vPvM components.

12.5. Results of PBT and vPvB assessment

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any PBT or vPvB components.

12.6. Endocrine disrupting properties

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any components that may cause endocrine disruption in the environment.

12.7. Other adverse effects

Not available.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

SECTION 14: Transport information**14.1. UN number or ID number**

UN 1759

ALCON (TI) PLASTIC METAL BOND EPOXY & TITANIUM (PUTTY) - CATALYST

Creation date	01st March 2021	Version	3.0
Revision date	16th December 2025		

14.2. UN proper shipping name

CORROSIVE SOLID, N.O.S.

14.3. Transport hazard class(es)

8 Corrosive substances

14.4. Packing group

I

14.5. Environmental hazards

not relevant

14.6. Special precautions for user

Reference in the Sections 4 to 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant

Additional information

Hazard identification No.

88

UN number

1759

Classification code

C10

Safety signs

8

**Road transport - ADR**

Special provisions

274

Limited quantities

0

Excepted quantities

E0

Packaging

Packing instructions

P002, IBC07

Mixed packing provisions

MP18

Portable tanks and bulk containers

Guidelines

T6

Special provisions

TP33

ADR tank

Tank code

S10AN, L10BH

Vehicles for tank carriage

AT

Transport category

1

Tunnel restriction code

(E)

Special provision for

packages

V10

operation

S20

ALCON (TI) PLASTIC METAL BOND EPOXY & TITANIUM (PUTTY) - CATALYST

Creation date	01st March 2021	Version	3.0
Revision date	16th December 2025		

Railway transport - RID

Special provisions 274

Packaging

Packing instructions P002, IBC07

Mixed packing provisions MP18

Portable tanks and bulk containers

Guidelines T6

Special provisions TP33

RID Tanks

Tank code S10AN, L10BH

Transport category 1

Special provision for

packages W10

Air transport - ICAO/IATA

Packaging instructions for limited amount Forbidden

Packaging instructions passenger 858

Cargo packaging instructions 862

Marine transport - IMDG

EmS (emergency plan) F-A, S-B

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

not available

SECTION 16: Other information**A list of standard risk phrases used in the safety data sheet**

EUH208	Contains Not classified. May produce an allergic reaction.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
H302	Harmful if swallowed.
H302+H332	Harmful if swallowed or if inhaled.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H351	Suspected of causing cancer if inhaled.
H412	Harmful to aquatic life with long lasting effects.

Guidelines for safe handling used in the safety data sheet

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P264	Wash face, hands and exposed parts of the body thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ALCON (TI) PLASTIC METAL BOND EPOXY & TITANIUM (PUTTY) - CATALYST

Creation date	01st March 2021	Version	3.0
Revision date	16th December 2025		

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P312	IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a doctor.
P501	Dispose of contents/container to by handing over to the person authorized to dispose of waste or by returning to the supplier.

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

Acute Tox.	Acute toxicity
ADR	Agreement concerning the international carriage of dangerous goods by road
Aquatic Chronic	Hazardous to the aquatic environment (chronic)
ATE	Acute toxicity estimate
BCF	Bioconcentration Factor
Carc.	Carcinogenicity
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
EC	Identification code for each substance listed in EINECS
EC ₅₀	Concentration of a substance when it is affected 50 % of the population
EINECS	European Inventory of Existing Commercial Chemical Substances
EmS	Emergency Response Procedures for Ships Carrying Dangerous Goods
EU	European Union
EuPCS	European Product Categorisation System
Eye Dam.	Serious eye damage
Eye Irrit.	Eye irritation
IATA	International Air Transport Association
IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization
IUPAC	International Union of Pure and Applied Chemistry
LC ₅₀	Lethal concentration of a substance in which it can be expected death of 50% of the population
LD ₅₀	Lethal dose of a substance in which it can be expected death of 50% of the population
log K _{ow}	Octanol-water partition coefficient
NOEC	No observed effect concentration
OEL	Occupational Exposure Limits
PBT	Persistent, bioaccumulative and toxic
PMT	Persistent, mobile and toxic
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulation concerning the International Carriage of Dangerous Goods by Rail
Skin Corr.	Skin corrosion
Skin Irrit.	Skin irritation



SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ALCON (TI) PLASTIC METAL BOND EPOXY & TITANIUM (PUTTY) - CATALYST

Creation date	01st March 2021	Version	3.0
Revision date	16th December 2025		

Skin Sens.	Skin sensitization
UN number	Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB	Substances of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very persistent and very bioaccumulative
vPvM	Very persistent and very mobile

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended.
REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

More information

Classification procedure - calculation method.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.