

ALCON (TI) PLASTIC METAL BOND EPOXY & TITANIUM (PUTTY) - RESIN

Creation date	01st March 2021	Version	3.0
Revision date	16th December 2025		

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. **Product identifier**
ALCON (TI) PLASTIC METAL BOND EPOXY & TITANIUM (PUTTY) - RESIN
Substance / mixture mixture
Number M-2234
- 1.2. **Relevant identified uses of the substance or mixture and uses advised against**
Mixture's intended use
Resin
Mixture uses advised against
The product should not be used in ways other than those referred in Section 1.
- 1.3. **Details of the supplier of the safety data sheet**
Manufacturer
Name or trade name ALCON ENDÜSTRİYEL ÜRÜNLER SAN. VE TİC. LTD. ŞTİ.
Address SOĞANLIK YENİ MAH. ALİAĞA SOK. NO:8 DAİRE:37 Bumerang
Kartal Rezidans Kartal, İstanbul, 34880
Turkey
Phone +90 216 661 00 90
Email alcon@alcon.com.tr
Web address www.alcon.com.tr
- 1.4. **Emergency telephone number**
European emergency number: 112

SECTION 2: Hazards identification

- 2.1. **Classification of the substance or mixture**
Classification of the mixture in accordance with Regulation (EC) No 1272/2008
The mixture is classified as dangerous.

Skin Irrit. 2, H315
Skin Sens. 1, H317
Eye Irrit. 2, H319
Aquatic Chronic 3, H412
Most serious adverse effects on human health and the environment
Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful to aquatic life with long lasting effects.
- 2.2. **Label elements**
Hazard pictogram

Signal word
Warning
Hazardous substances
silicon carbide fibres (with diameter < 3 µm, length > 5 µm and aspect ratio ≥ 3:1)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.
titanium dioxide
Hazard statements
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ALCON (TI) PLASTIC METAL BOND EPOXY & TITANIUM (PUTTY) - RESIN

Creation date 01st March 2021 Version 3.0
Revision date 16th December 2025

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P201 Obtain special instructions before use.
P264 Wash hands and exposed parts of the body thoroughly after handling.
P273 Avoid release to the environment.
P280 Wear eye protection/protective gloves/protective clothing.
P302+P352 IF ON SKIN: Wash with plenty of water and soap.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P405 Store locked up.
P501 Dispose of contents/container to by handing over to the person authorized to dispose of waste or by returning to the supplier.

Supplemental information

EUH205 Contains epoxy constituents. May produce an allergic reaction.
EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended. Does not contain any PMT or vPvM components.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 014-048-00-5 CAS: 409-21-2 EC: 206-991-8	silicon carbide fibres (with diameter < 3 µm, length > 5 µm and aspect ratio ≥ 3:1)	40-50	Carc. 1B, H350i (inhalation) EUH208	4
Index: 603-074-00-8 CAS: 25068-38-6 EC: 500-033-5	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	10-20	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 Aquatic Chronic 2, H411 Specific concentration limit: Skin Irrit. 2, H315: C ≥ 5 % Eye Irrit. 2, H319: C ≥ 5 %	
Index: 603-103-00-4 CAS: 68609-97-2 EC: 271-846-8	oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	10-20	Skin Irrit. 2, H315 Skin Sens. 1, H317	
Index: 022-006-00-2 CAS: 13463-67-7 EC: 236-675-5	titanium dioxide	5-10	Carc. 2, H351 (inhalation) EUH208	1, 2, 3

ALCON (TI) PLASTIC METAL BOND EPOXY & TITANIUM (PUTTY) - RESIN

Creation date	01st March 2021	Version	3.0
Revision date	16th December 2025		

Notes

- Note V: If the substance is to be placed on the market as fibres (with diameter < 3 µm, length > 5 µm and aspect ratio ≥ 3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied.*
- Note W: It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung.*

This note aims to describe the particular toxicity of the substance; it does not constitute a criterion for classification according to this Regulation.

- Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 µm.*
- The use of the substance is restricted by Annex XVII of REACH Regulation*

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures**

Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet.

If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Protect the person against growing cold. Provide medical treatment if irritation, dyspnoea or other symptoms persist.

If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible. Soap, soap solution or shampoo should be used if there is no skin injury. Provide medical treatment if skin irritation persists.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Rinsing should continue at least for 10 minutes. Provide medical treatment, specialized if possible.

If swallowed

Rinse out the mouth with water and provide 0.2-0.5 L of water. Provide medical treatment if the person has any health problems.

4.2. Most important symptoms and effects, both acute and delayed**If inhaled**

Not expected.

If on skin

May cause an allergic skin reaction.

If in eyes

Causes serious eye irritation.

If swallowed

Irritation, nausea.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

Unsuitable extinguishing media

Water - full jet.

5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

ALCON (TI) PLASTIC METAL BOND EPOXY & TITANIUM (PUTTY) - RESIN

Creation date	01st March 2021	Version	3.0
Revision date	16th December 2025		

5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Prevent contact with skin and eyes.

6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

6.4. Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Prevent contact with skin and eyes. Contaminated work clothing should not be allowed out of the workplace. Wash hands and exposed parts of the body thoroughly after handling. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection. Avoid release to the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose.

7.3. Specific end use(s)

not available

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

The mixture contains no substances for which occupational exposure limits are set.

8.2. Exposure controls

Take off contaminated clothing and wash before reuse. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

Eye/face protection

Protective goggles.

Skin protection

Hand protection: Protective gloves resistant to the product. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Observe other recommendations of the manufacturer. Other protection: protective workwear. Contaminated skin should be washed thoroughly.



SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ALCON (TI) PLASTIC METAL BOND EPOXY & TITANIUM (PUTTY) - RESIN

Creation date 01st March 2021 Version 3.0
Revision date 16th December 2025

Glove material	Thickness	Breakthrough time	Class
Neoprene (CR)	≥ 0.7 mm	>480 min	6

Respiratory protection

It is not needed.

Thermal hazard

Not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	liquid
Colour	black
Odour	Characteristic
Melting point/freezing point	data not available
Boiling point or initial boiling point and boiling range	data not available
Flammability	data not available
Lower and upper explosion limit	data not available
Flash point	data not available
Auto-ignition temperature	data not available
Decomposition temperature	data not available
pH	data not available
Kinematic viscosity	data not available
Solubility in water	data not available
Partition coefficient n-octanol/water (log value)	data not available
Vapour pressure	data not available
Density and/or relative density	data not available
Relative vapour density	data not available
Particle characteristics	data not available
Form	liquid - solid: mixture of, paste

9.2. Other information

not available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Unknown.

10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost.

10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

ALCON (TI) PLASTIC METAL BOND EPOXY & TITANIUM (PUTTY) - RESIN

Creation date 01st March 2021 Version 3.0
 Revision date 16th December 2025

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

No toxicological data is available for the mixture.

Acute toxicity

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)						
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex
Oral	LD ₅₀	OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)	>2000 mg/kg		Rat (None)	F
Dermal	LD ₅₀	OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))	>2000 mg/kg		Rat (None)	

titanium dioxide						
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex
Oral	LD ₅₀	OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure), Guideline: EPA OPPTS 870.1100 (Acute Oral Toxicity)	>5000 mg/kg		Rat (None)	F

Skin corrosion/irritation

Causes skin irritation.

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)				
Route of exposure	Value	Result	Exposure time	Species
	Causes skin irritation.	Irritating		None

Serious eye damage/irritation

Causes serious eye irritation.

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)				
Route of exposure	Value	Result	Exposure time	Species
	Causes serious eye irritation.	Serious eye damage		None



SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ALCON (TI) PLASTIC METAL BOND EPOXY & TITANIUM (PUTTY) - RESIN

Creation date 01st March 2021 Version 3.0
Revision date 16th December 2025

Respiratory or skin sensitisation

May cause an allergic skin reaction.

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)				
Route of exposure	Result	Exposure time	Species	Sex
	Sensitizing		None	

Germ cell mutagenicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Carcinogenicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Reproductive toxicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Toxicity for specific target organ - single exposure

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.



SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ALCON (TI) PLASTIC METAL BOND EPOXY & TITANIUM (PUTTY) - RESIN

Creation date 01st March 2021 Version 3.0
Revision date 16th December 2025

Toxicity for specific target organ - repeated exposure

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)							
Route of exposure	Parameter	Method	Value	Exposure time	Result	Species	Sex
Oral	NOAEL	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity) , Guideline: other:MITI, Japanese ministry of international trade and industry, February 1998, Remarks on results: other:Effect type: toxicity (migrated information)	15 mg/kg bw	2 years		Rat (None)	M



SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ALCON (TI) PLASTIC METAL BOND EPOXY & TITANIUM (PUTTY) - RESIN

Creation date 01st March 2021 Version 3.0
Revision date 16th December 2025

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)							
Route of exposure	Parameter	Method	Value	Exposure time	Result	Species	Sex
Oral	NOAEL	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other:MITI, Japanese ministry of international trade and industry, February 1998, Remarks on results: other:Effect type: toxicity (migrated information)	100 mg/kg bw	2 years		Rat (None)	F
Oral	NOAEL	OECD Guideline 408 (Repeated Dose 90- Day Oral Toxicity in Rodents), Guideline: EPA OPPTS 870.3100 (90- Day Oral Toxicity in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: other:japanese MITI guidelines for toxicity testing of chemicals	50 mg/kg bw	90 days		Rat (None)	

ALCON (TI) PLASTIC METAL BOND EPOXY & TITANIUM (PUTTY) - RESIN

Creation date	01st March 2021	Version	3.0
Revision date	16th December 2025		

Aspiration hazard

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

11.2. Information on other hazards**Endocrine disrupting properties**

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any components that may cause endocrine disruption for humans.

Other information

not available

SECTION 12: Ecological information**12.1. Toxicity**

Harmful to aquatic life with long lasting effects.

Acute toxicity

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)				
Parameter	Value	Exposure time	Species	Environment
LC ₅₀	1.2 mg/l		Fish (Oncorhynchus mykiss)	
EC ₅₀	9.4 mg/l	72 hours	Algae (Scenedesmus capricornutum)	
EC ₅₀	>11 mg/l	72 hours	Algae (Scenedesmus capricornutum)	

titanium dioxide				
Parameter	Value	Exposure time	Species	Environment
LC ₅₀	155 mg/l		Fish (other: Japanese Medaka)	
EC ₅₀	19.3 mg/l		Crustaceans (Daphnia magna)	
EC ₅₀	27.8 mg/l		Crustaceans (Daphnia magna)	
EC ₅₀	>100 mg/l	72 hours	Algae (Pseudokirchneriella subcapitata)	

Chronic toxicity

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)				
Parameter	Value	Exposure time	Species	Environment
LOEC	1 mg/l		Daphnia (Daphnia magna)	
NOEC	0.3 mg/l		Daphnia (Daphnia magna)	

silicon carbide fibres (with diameter < 3 µm, length > 5 µm and aspect ratio ≥ 3:1)				
Parameter	Value	Exposure time	Species	Environment
LOEC	100 mg/l		Daphnia (Daphnia magna)	

titanium dioxide				
Parameter	Value	Exposure time	Species	Environment
NOEC	≥100 mg/l		Daphnia (Daphnia magna)	

ALCON (TI) PLASTIC METAL BOND EPOXY & TITANIUM (PUTTY) - RESIN

Creation date	01st March 2021	Version	3.0
Revision date	16th December 2025		

titanium dioxide				
Parameter	Value	Exposure time	Species	Environment
NOEC	≥2.92 mg/l		Daphnia (Daphnia magna)	

12.2. Persistence and degradability

No data are available for either the mixture or the components.

12.3. Bioaccumulative potential

No data are available for either the mixture or the components.

12.4. Mobility in soil

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any PMT or vPvM components.

12.5. Results of PBT and vPvB assessment

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any PBT or vPvB components.

12.6. Endocrine disrupting properties

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any components that may cause endocrine disruption in the environment.

12.7. Other adverse effects

Not available.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

SECTION 14: Transport information**14.1. UN number or ID number**

not subject to transport regulations

14.2. UN proper shipping name

not relevant

14.3. Transport hazard class(es)

not relevant

14.4. Packing group

not relevant

14.5. Environmental hazards

not relevant

14.6. Special precautions for user

Reference in the Sections 4 to 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant

ALCON (TI) PLASTIC METAL BOND EPOXY & TITANIUM (PUTTY) - RESIN

Creation date	01st March 2021	Version	3.0
Revision date	16th December 2025		

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

Restrictions pursuant to Annex XVII of Regulation (EC) No. 1907/2006 (REACH), as amended

silicon carbide fibres (with diameter < 3 µm, length > 5 µm and aspect ratio ≥ 3:1)

Restriction	Conditions of restriction
28	1. Shall not be placed on the market, or used, — as substances, — as constituents of other substances, or, — in mixtures, for supply to the general public when the individual concentration in the substance or mixture is equal to or greater than: — either the relevant specific concentration limit specified in Part 3 of Annex VI to Regulation (EC) No 1272/2008, - or, — the relevant generic concentration limit specified in Part 3 of Annex I of Regulation (EC) No 1272/2008. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that the packaging of such substances and mixtures is marked visibly, legibly and indelibly as follows: “Restricted to professional users”. 2. By way of derogation, paragraph 1 shall not apply to: (a) medicinal or veterinary products as defined by Directive 2001/82/EC and Directive 2001/83/EC; (b) cosmetic products as defined by Directive 76/768/EEC; (c) the following fuels and oil products: — motor fuels which are covered by Directive 98/70/EC, — mineral oil products intended for use as fuel in mobile or fixed combustion plants, — fuels sold in closed systems (e.g. liquid gas bottles); (d) artists' paints covered by Regulation (EC) No 1272/2008; (e) the substances listed in Appendix 11, column 1, for the applications or uses listed in Appendix 11, column 2. Where a date is specified in column 2 of Appendix 11, the derogation shall apply until the said date. (f) devices covered by Regulation (EU) 2017/745.

15.2. Chemical safety assessment

not available

SECTION 16: Other information

A list of standard risk phrases used in the safety data sheet

EUH205	Contains epoxy constituents. May produce an allergic reaction.
EUH208	Contains Not classified. May produce an allergic reaction.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H350i	May cause cancer by inhalation.
H351	Suspected of causing cancer if inhaled.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ALCON (TI) PLASTIC METAL BOND EPOXY & TITANIUM (PUTTY) - RESIN

Creation date	01st March 2021	Version	3.0
Revision date	16th December 2025		

Guidelines for safe handling used in the safety data sheet

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P201	Obtain special instructions before use.
P264	Wash hands and exposed parts of the body thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear eye protection/protective gloves/protective clothing.
P302+P352	IF ON SKIN: Wash with plenty of water and soap.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P405	Store locked up.
P501	Dispose of contents/container to by handing over to the person authorized to dispose of waste or by returning to the supplier.

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

ADR	Agreement concerning the international carriage of dangerous goods by road
Aquatic Chronic	Hazardous to the aquatic environment (chronic)
BCF	Bioconcentration Factor
Carc.	Carcinogenicity
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
EC	Identification code for each substance listed in EINECS
EC ₅₀	Concentration of a substance when it is affected 50 % of the population
EINECS	European Inventory of Existing Commercial Chemical Substances
EmS	Emergency Response Procedures for Ships Carrying Dangerous Goods
EU	European Union
EuPCS	European Product Categorisation System
Eye Irrit.	Eye irritation
IATA	International Air Transport Association
IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization
IUPAC	International Union of Pure and Applied Chemistry
LC ₅₀	Lethal concentration of a substance in which it can be expected death of 50% of the population
LD ₅₀	Lethal dose of a substance in which it can be expected death of 50% of the population
log Kow	Octanol-water partition coefficient
NOAEL	No observed adverse effect level
NOEC	No observed effect concentration
OEL	Occupational Exposure Limits
PBT	Persistent, bioaccumulative and toxic
PMT	Persistent, mobile and toxic
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals



SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ALCON (TI) PLASTIC METAL BOND EPOXY & TITANIUM (PUTTY) - RESIN

Creation date	01st March 2021	Version	3.0
Revision date	16th December 2025		

RID	Regulation concerning the International Carriage of Dangerous Goods by Rail
Skin Irrit.	Skin irritation
Skin Sens.	Skin sensitization
UN number	Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB	Substances of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very persistent and very bioaccumulative
vPvM	Very persistent and very mobile

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended.
REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

More information

Classification procedure - calculation method.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.