

ALCON TIRE REPAIR SPRAY

Creation date	25th November 2020	Version	3.0
Revision date	02nd December 2025		

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. **Product identifier** ALCON TIRE REPAIR SPRAY
Substance / mixture mixture
Number M-7722 / M-9016
- 1.2. **Relevant identified uses of the substance or mixture and uses advised against**
Mixture's intended use
Tire Repair and Inflating Spray can be used in all passenger cars, motorcycles, bicycles, light commercial vehicles or caravans.
Mixture uses advised against
The product should not be used in ways other than those referred in Section 1.
- 1.3. **Details of the supplier of the safety data sheet**
Manufacturer
Name or trade name ALCON ENDÜSTRİYEL ÜRÜNLER SAN. VE TİC. LTD. ŞTİ.
Address SOĞANLIK YENİ MAH. ALİAĞA SOK. NO:8 DAİRE:37 Bumerang
Kartal Rezidans Kartal, İstanbul, 34880
Turkey
Phone +90 216 661 00 90
Email alcon@alcon.com.tr
Web address www.alcon.com.tr
- 1.4. **Emergency telephone number**
European emergency number: 112

SECTION 2: Hazards identification

- 2.1. **Classification of the substance or mixture**
Classification of the mixture in accordance with Regulation (EC) No 1272/2008
The mixture is classified as dangerous.
- Aerosol 1, H222, H229
Skin Irrit. 2, H315
Eye Dam. 1, H318
Aquatic Chronic 3, H412
- Most serious adverse physico-chemical effects**
Extremely flammable aerosol. Pressurised container: May burst if heated.
- Most serious adverse effects on human health and the environment**
Causes severe skin burns and eye damage. Causes serious eye damage. Harmful to aquatic life with long lasting effects.
- 2.2. **Label elements**
Hazard pictogram
-
- Signal word**
Danger
- Hazardous substances**
butane
propane
isobutane
ammonia, anhydrous
- Hazard statements**
H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ALCON TIRE REPAIR SPRAY

Creation date	25th November 2020	Version	3.0
Revision date	02nd December 2025		

H315 Causes skin irritation.
H318 Causes serious eye damage.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P264 Wash face, hands and exposed parts of the body thoroughly after handling.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P405 Store locked up.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
P501 Dispose of contents/container to be handed over to the person authorized to dispose of waste or by returning to the supplier.
P305+P351+P338+P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended. Does not contain any PMT or vPvM components.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 601-004-00-0 CAS: 106-97-8 EC: 203-448-7	butane	15-35	Press. Gas, Flam. Gas 1, H220	1, 2
Index: 601-003-00-5 CAS: 74-98-6 EC: 200-827-9	propane	10-20	Press. Gas, Flam. Gas 1, H220	2, 3
Index: 601-004-00-0 CAS: 75-28-5 EC: 200-857-2	isobutane	1-10	Press. Gas, Flam. Gas 1, H220	1, 2
Index: 007-001-00-5 CAS: 7664-41-7 EC: 231-635-3	ammonia, anhydrous	0.1-5	Press. Gas, Flam. Gas 2, H221 Skin Corr. 1B, H314 Acute Tox. 3, H331 Aquatic Acute 1, H400 (M=1)	2, 3

Notes

- 1 Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

ALCON TIRE REPAIR SPRAY

Creation date	25th November 2020	Version	3.0
Revision date	02nd December 2025		

- 2 *Note U (Table 3): When put on the market gases have to be classified as "Gases under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned:*

Press. Gas (Comp.)
Press. Gas (Liq.)
Press. Gas (Ref. Liq.)
Press. Gas (Diss.)

Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).

- 3 *A substance for which exposure limits are set.*

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures**

If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet.

If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Take care of your own safety, do not let the affected person walk! Beware of the contaminated clothes.

If on skin

Remove contaminated clothes. Take off any rings, watches, bracelets before or during washing if worn in the contaminated areas of the skin. Rinse contaminated areas with a flow of water, lukewarm at best, for 10-30 minutes; do not use any brush, soap or neutralizers. Depending on the situation, call the medical rescue service and always ensure medical treatment.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. No neutralization should be performed in any case! Rinsing should be continued for 10-30 minutes from the inner to the outer eye corner to make sure that the other eye is not involved. Depending on the situation, call medical rescue service or ensure medical treatment as promptly as possible. Everyone must be referred for treatment even if affected only a little.

If swallowed

Unlikely. RINSE THE MOUTH WITH WATER IMMEDIATELY AND LET THE PERSON DRINK 0.2-0.5 l of cold water to reduce the heating effect of the corrosive substance. Consuming larger amounts of liquid is not advisable as it may induce vomiting and potential inhaling of the corrosive substances in the lungs. The affected person must not be forced to drink, particularly if already feeling pain in the mouth or throat. In this case let the affected person only rinse the mouth with water. DO NOT PROVIDE ACTIVATED CARBON! Depending on the situation, call medical rescue service or ensure medical treatment as promptly as possible.

4.2. Most important symptoms and effects, both acute and delayed**If inhaled**

Inhaling vapours can cause corrosion of the breathing system.

If on skin

Causes severe skin burns.

If in eyes

Causes serious eye damage.

If swallowed

Corrosion of the digestion system can occur.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

Unsuitable extinguishing media

Water - full jet.

ALCON TIRE REPAIR SPRAY

Creation date	25th November 2020	Version	3.0
Revision date	02nd December 2025		

5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Provide sufficient ventilation. Extremely flammable aerosol. Pressurised container: May burst if heated. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale aerosols. Prevent contact with skin and eyes.

6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

6.4. Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Do not inhale aerosols. Prevent contact with skin and eyes. No smoking. Protect against direct sunlight. Do not pierce or burn, even after use. Wash hands and exposed parts of the body thoroughly after handling. Do not spray on an open flame or other ignition source. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection. Avoid release to the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

7.3. Specific end use(s)

not available

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

The mixture contains substances for which occupational exposure limits are set.

European Union**Commission Directive 2000/39/EC**

Substance name (component)	Type	Value
ammonia, anhydrous (CAS: 7664-41-7)	OEL 8 hours	14 mg/m ³
	OEL 8 hours	20 ppm
	OEL 15 minutes	36 mg/m ³
	OEL 15 minutes	50 ppm

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ALCON TIRE REPAIR SPRAY

Creation date 25th November 2020 Version 3.0
 Revision date 02nd December 2025

Turkey

Substance name (component)	Type	Value
propane (CAS: 74-98-6)	TWA (8 hours)	1800 mg/m ³
	TWA (8 hours)	1000 ppm
ammonia, anhydrous (CAS: 7664-41-7)	TWA (8 hours)	14 mg/m ³
	TWA (8 hours)	20 ppm
	STEL (15 min.)	36 mg/m ³
	STEL (15 min.)	50 ppm

8.2. Exposure controls

Take off contaminated clothing and wash before reuse. Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

Eye/face protection



Protective goggles or face shield (based on the nature of the work performed).

Skin protection



Hand protection: Protective gloves resistant to the product. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. When selecting gloves, consider the properties of the product and the duration of exposure. Replace gloves at the first signs of wear or damage. Other protection: Protective antistatic clothing made of natural fibres (cotton) or synthetic fibres resistant to elevated temperatures. Antistatic footwear. Contaminated skin should be washed thoroughly.

Glove material	Thickness	Breakthrough time	Class	Exposure time
Nitrile (NBR)	≥ 0.3 mm	>30 min	2	Short-term
Nitrile (NBR)	≥ 0.7 mm	>480 min	6	Repeated, Long-term

Respiratory protection



Halfmask with a filter against organic vapours or a self-contained breathing apparatus as appropriate if exposure limit values of substances are exceeded or in a poorly ventilated environment. Respirator.

Thermal hazard

Not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ALCON TIRE REPAIR SPRAY

Creation date	25th November 2020	Version	3.0
Revision date	02nd December 2025		

Physical state	liquid
Colour	colourless
Odour	Characteristic
Melting point/freezing point	data not available
Boiling point or initial boiling point and boiling range	data not available
Flammability	data not available
Lower and upper explosion limit	data not available
Flash point	data not available
Auto-ignition temperature	data not available
Decomposition temperature	data not available
pH	9-11 (undiluted)
Kinematic viscosity	data not available
Solubility in water	data not available
Partition coefficient n-octanol/water (log value)	data not available
Vapour pressure	data not available
Density and/or relative density	
Density	0.9-1 g/cm ³
Relative vapour density	data not available
Particle characteristics	data not available

9.2. Other information

not available

SECTION 10: Stability and reactivity**10.1. Reactivity**

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Unknown.

10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost.
Pressurised container: May burst if heated.

10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Hazardous substances in concentrations exceeding exposure limits may cause acute inhalation poisoning, depending on the concentration and duration of exposure. No toxicological data is available for the mixture.

Acute toxicity

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

ALCON TIRE REPAIR SPRAY						
Route of exposure	Parameter	Value	Exposure time	Species	Sex	Value determination
Inhalation (vapor)	ATE	75 mg/l				Calculation of value



SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ALCON TIRE REPAIR SPRAY

Creation date 25th November 2020 Version 3.0
Revision date 02nd December 2025

ammonia, anhydrous						
Route of exposure	Parameter	Value	Exposure time	Species	Sex	Value determination
Oral	LD ₅₀	350 mg/kg		Rat (None)	M	

Skin corrosion/irritation

Causes severe skin burns and eye damage. Data for the components of the mixture are not available.

Serious eye damage/irritation

Causes severe skin burns and eye damage. Causes serious eye damage. Data for the components of the mixture are not available.

Respiratory or skin sensitisation

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Germ cell mutagenicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Carcinogenicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Reproductive toxicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Toxicity for specific target organ - single exposure

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Toxicity for specific target organ - repeated exposure

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

Repeated dose toxicity

ammonia, anhydrous						
Route of exposure	Parameter	Result	Value	Exposure time	Species	Sex
Oral	NOAEL		256 mg/kg	2 years	Rat (None)	M
Oral	NOAEL		284 mg/kg	2 years	Rat (None)	F

Aspiration hazard

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

11.2. Information on other hazards

not available

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.



SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ALCON TIRE REPAIR SPRAY

Creation date 25th November 2020 Version 3.0
Revision date 02nd December 2025

Acute toxicity

ammonia, anhydrous				
Parameter	Value	Exposure time	Species	Environment
LC ₅₀	0.75-3.4 mg/l		Fish (Pimephales promelas)	
LC ₅₀	34-109 mg/l		Fish (Pimephales promelas)	

Chronic toxicity

ammonia, anhydrous				
Parameter	Value	Exposure time	Species	Environment
LOEC(chronic)	1.3 mg/l	96 hours	Daphnia (Daphnia magna)	
NOEC(chronic)	0.79 mg/l	96 hours	Daphnia (Daphnia magna)	
NOECchronic fish	1.2 mg/l	61 days	Fish (Oncorhynchus gorbuscha)	

12.2. Persistence and degradability

No data are available for either the mixture or the components.

12.3. Bioaccumulative potential

No data are available for either the mixture or the components.

12.4. Mobility in soil

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any PMT or vPvM components.

12.5. Results of PBT and vPvB assessment

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any PBT or vPvB components.

12.6. Endocrine disrupting properties

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any components that may cause endocrine disruption in the environment.

12.7. Other adverse effects

Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

SECTION 14: Transport information

14.1. UN number or ID number

UN 1950

14.2. UN proper shipping name

AEROSOLS

14.3. Transport hazard class(es)

2 Gases

14.4. Packing group

not relevant

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ALCON TIRE REPAIR SPRAY

Creation date	25th November 2020	Version	3.0
Revision date	02nd December 2025		

14.5. Environmental hazards

not relevant

14.6. Special precautions for user

Reference in the Sections 4 to 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant


Additional information

Hazard identification No.

UN number

Classification code

Safety signs



5FC

2.1+8

**Road transport - ADR**

Special provisions

190, 327, 344, 625

Limited quantities

1 L

Excepted quantities

E0

Packaging

Packing instructions

P207, LP200

Special packing provisions

PP87, RR6, L2

Mixed packing provisions

MP9

Transport category

1

Tunnel restriction code

(D)

Special provision for

packages

V14

loading, unloading and handling

CV9, CV12

operation

S2

Railway transport - RID

Special provisions

190, 327, 344, 625

Packaging

Packing instructions

P207, LP200

Special packing provisions

PP87, RR6, L2

Mixed packing provisions

MP9

Transport category

1

Special provision for

packages

W14

loading, unloading and handling

CW9, CW12

Marine transport - IMDG

EmS (emergency plan)

F-D, S-U

MFAG

620

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ALCON TIRE REPAIR SPRAY

Creation date	25th November 2020	Version	3.0
Revision date	02nd December 2025		

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

not available

SECTION 16: Other information

A list of standard risk phrases used in the safety data sheet

H220	Extremely flammable gas.
H221	Flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H400	Very toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

Guidelines for safe handling used in the safety data sheet

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P264	Wash face, hands and exposed parts of the body thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P405	Store locked up.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
P501	Dispose of contents/container to be handing over to the person authorized to dispose of waste or by returning to the supplier.
P305+P351+P338+P310	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

Acute Tox.	Acute toxicity
ADR	Agreement concerning the international carriage of dangerous goods by road
Aerosol	Aerosol
Aquatic Acute	Hazardous to the aquatic environment
Aquatic Chronic	Hazardous to the aquatic environment (chronic)

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ALCON TIRE REPAIR SPRAY

Creation date	25th November 2020	Version	3.0
Revision date	02nd December 2025		

ATE	Acute toxicity estimate
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
EC	Identification code for each substance listed in EINECS
EINECS	European Inventory of Existing Commercial Chemical Substances
EmS	Emergency Response Procedures for Ships Carrying Dangerous Goods
EU	European Union
EuPCS	European Product Categorisation System
Eye Dam.	Serious eye damage
Flam. Gas	Flammable gas
IATA	International Air Transport Association
IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization
IUPAC	International Union of Pure and Applied Chemistry
LC ₅₀	Lethal concentration of a substance in which it can be expected death of 50% of the population
LD ₅₀	Lethal dose of a substance in which it can be expected death of 50% of the population
log Kow	Octanol-water partition coefficient
NOAEL	No observed adverse effect level
NOEC	No observed effect concentration
OEL	Occupational Exposure Limits
PBT	Persistent, bioaccumulative and toxic
PMT	Persistent, mobile and toxic
ppm	Parts per million
Press. Gas (Comp.)	Gas under pressure: compressed gas
Press. Gas (Diss.)	Gas under pressure: dissolved gas
Press. Gas (Liq.)	Gas under pressure: liquefied gas
Press. Gas (Ref. Liq.)	Gas under pressure: refrigerated liquefied gas
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulation concerning the International Carriage of Dangerous Goods by Rail
Skin Corr.	Skin corrosion
Skin Irrit.	Skin irritation
UN number	Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB	Substances of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very persistent and very bioaccumulative
vPvM	Very persistent and very mobile

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet



SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

ALCON TIRE REPAIR SPRAY

Creation date	25th November 2020	Version	3.0
Revision date	02nd December 2025		

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended.
REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the
manufacturer of the substance / mixture, if available - information from registration dossiers.

More information

Classification procedure - calculation method.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The
provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The
information should not be understood as guaranteeing the suitability and usability of the product for a particular application.