



TECHNICAL DATA SHEET

M-9810 ALCON MULTI LUBE WR 2 BEARING GREASE

Product Description

It is a mixed product and its oiling feature was strengthened with lubricant molybdenum disulfide. It is high performance grease and resistant to high pressure.

Application Areas

It is used in industrial areas where there are medium and high loads, electric and water pump motors, automobile, commercial and off-road vehicles, wheel bearings of agricultural and work machines and central lubrication systems and so on.

Specifications

- Durable of working under load
- Accurate protection against corrosion and depreciation
- High resistance to washing, water and humidity
- Long protection against oxidation and corrosion
- Long time oiling

Revision Date : 27.02.2019

Version no : 01

Manufacturer reserves the right to amend product specifications.

ALCON Endüstriyel Ürünler San. ve Tic. Ltd. Şti.

Adres: Ferhatpaşa Mh. Kocasınan Cd. 11.Sk. No:45 ATAŞEHİR – İSTANBUL

Tel : 0216 – 661 00 90 (Pbx) Faks : 0216 – 661 01 57

www.alcon.com.tr



Color and Technical Properties

Color: Grey-Black

Relative Density: -

pH: -

NLGI: 2

Soap Species: Lithium

Processed Penetration(25 ° C, 60 strokes): 265 - 295 (ASTM D 217)

Drip Point (° C): min 180 (ASTM D 566)

Oil Breakdown (%) (40 ° C, 18h): max . 5 (IP 121)

Package Options

CODE	PRODUCT NAME	PACKING	PARCEL
M-9810	ALCON MULTI LUBE WR 2 BEARING GREASE	1000 gr. BOX	12

Warnings

S2 Keep out of reach of children.

S24 / 25 Avoid contact with eyes and skin.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S28 After contact with skin, wash immediately with soap and plenty of water.

S29 / 56 Do not empty into sewer. Waste and cabin collection of dangerous or special waste ,dispose of them in place.

S37 / 39 Wear suitable gloves and eye / face protection.

S61 Avoid release to the environment. Refer to special instructions / Safety Data Sheet.

Revision Date : 27.02.2019

Version no : 01

Manufacturer reserves the right to amend product specifications.

ALCON Endüstriyel Ürünler San. ve Tic. Ltd. Şti.

Adres: Ferhatpaşa Mh. Kocasınan Cd. 11.Sk. No:45 ATAŞEHİR – İSTANBUL

Tel : 0216 – 661 00 90 (Pbx) Faks : 0216 – 661 01 57

www.alcon.com.tr



Shelf Life And Storage

Shelf life : 60 months

Must be stored in tightly closed original packaging. Store in a cool, dry, well-ventilated place. Keep away from materials, open flames, high temperatures and contact with oxidizing materials. Precautions should be taken against sources of ignition during filling and evacuation. Pump for static electricity not to accumulate. must be grounded or the transfer containers must be connected together by a cable. There is no fire hazard if stored at ambient temperature. It should be stored at temperatures between 0 °C and 50 °C.

Revision Date : 27.02.2019

Version no : 01

Manufacturer reserves the right to amend product specifications.

ALCON Endüstriyel Ürünler San. ve Tic. Ltd. Şti.

Adres: Ferhatpaşa Mh. Kocasınan Cd. 11.Sk. No:45 ATAŞEHİR – İSTANBUL

Tel : 0216 – 661 00 90 (Pbx) Faks : 0216 – 661 01 57

www.alcon.com.tr