



TECHNICAL DATA SHEET

ALCON SHELLAC UNIVERSAL GASKET BOND

1. Product Description

Gasket bond.

2. Properties

Universal Gasket Bond SHELLAC-based is used for sealing; leather, fiber, cylinder head, cork, paper, rubber, metal, repa, cardboard etc.

3. Technical Information

Form : Liquid
Colour : Brown
Odour : characteristic

4. Application Details

- * The surfaces to be used seal should be clean from grease, rust and moisture.
- * ALCON SHELLAC is applied as a thin film to the surfaces and it is heated for 8-10 min. in cold weather 15-20 min. wait and stick the seal carefully.

5. Packaging

| CODE | PRODUCT NAME | PACKING | PARCEL |
|--------|-------------------------------|---------------|--------|
| M-9904 | SHELLAC UNIVERSAL GASKET BOND | 50 ml. BOTTLE | 72 |

6. Shelf Life and Storage

Shelf life is 5 years from production date . Keep temperatures above 50 ° C and away from direct sunlight. Store in a cool, dry place. Keep containers closed and upright, protecting them from physical damage. Avoid static discharge.



7. Caution

Keep under lock and key and out of reach of children.

Avoid contact with skin

Rinse immediately with plenty of water and seek contact with eyes.

After contact with skin wash immediately with soap and water.

Suitable protective clothing, gloves and eye / face protection.

Consult a doctor immediately in case of accident or if you feel unwell.

Avoid release to the environment.

8. Health and Safety

For more information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet containing, physical, ecological, and toxicological and other safety related data.