



TECHNICAL DATA SHEET ALCON PRO-MIX

1. Product Description

Two component epoxy putty adhesive

2. Properties

Waterproof, provides permanent fillet
Easy to use
It is resistant to weak acid, oil, gas, and humidity
It is practical and very strength

3. Technical Information

Form	: Putty	
Colour		: Blue-Yellow (turns into green after mixing)
Odour		: characteristic
Heat Resistance		: -40°C - +200°C
Pulling Power		: 300 kg/cm
Pressure Resistance		: 800 kg/cm
Hardening time at room temperature		: 3 hours
Hardening time under water		: 3 hours
Expiration without mixing at room temperature	: 3 years	
Expiration without mixing at the fridge	: min. 5 years	

4. Application Details

Adhering stone, marble, wood, glass, ceramic and cement materials to each other
Filling bush and bearings
Repairing various fuel oils and water tanks etc
Filling mouldings
It adheres in 3 three hours under water
Long shelf life (5 years in refrigerator and 3 years at room temperature)

5. Packaging

CODE	PRODUCT NAME	PACKING	PARCEL
M-2217	PRO-MIX EPOXY PUTTY	40 gr. BOX	36
M-2207	PRO-MIX EPOXY PUTTY	80 gr. BOX	36



6. Shelf Life and Storage

Shelf life is 5 years from production date . Keep temperatures above 50 ° C and away from direct sunlight. Store in a cool, dry place. Keep containers closed and upright, protecting them from physical damage. Avoid static discharge.

7. Caution

Keep under lock and key and out of reach of children.

Avoid contact with skin

Rinse immediately with plenty of water and seek contact with eyes.

After contact with skin wash immediately with soap and water.

Suitable protective clothing, gloves and eye / face protection.

Consult a doctor immediately in case of accident or if you feel unwell.

Avoid release to the environment.

8. Health and Safety

For more information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet containing, physical, ecological, and toxicological and other safety related data.